

SQT

NASA CONTRACTOR REPORT

NASA CR-141432

SEAHT

# A COMPUTER PROGRAM FOR THE USE OF INTERSECTING ARCS OF ALTIMETER DATA FOR SEA SURFACE HEIGHT REFINEMENT

(NASA-CR-141432) SEAHT: A COMPUTER PROGRAM  
FOR THE USE OF INTERSECTING ARCS OF  
ALTIMETER DATA FOR SEA SURFACE HEIGHT  
REFINEMENT (Wolf Research and Development  
Corp.) 119 p HC A06/MF A01

N78-12511

Unclas

55113

CSCI 13B G3/43

C P Allen  
C F Martin

Prepared Under Contract No NAS6-2639 by

EG&G/Washington Analytical Services Center, Inc.  
Wolf Research & Development Group  
Clarke and Vine Streets  
Pocomoke City, Maryland 21851



National Aeronautics and  
Space Administration

**Wallops Flight Center**

Wallops Island, Virginia 23337  
AC 804 824-3411

November 1977

1 Report No NASA CR-141432		2 Government Accession No		3 Recipient's Catalog No	
4 Title and Subtitle SEAHT - A COMPUTER PROGRAM FOR THE USE OF INTERSECTING ARCS OF ALTIMETER DATA FOR SEA SURFACE HEIGHT REFINEMENT				5 Report Date November 1977	
				6 Performing Organization Code	
7 Author(s) C. P. Allen and C. F. Martin				8 Performing Organization Report No	
9 Performing Organization Name and Address EG&G/Washington Analytical Services Center, Inc. Wolf Research & Development Group Clarke and Vine Streets Pocomoke City, Maryland 21851				10 Work Unit No	
				11 Contract or Grant No NAS6-2639	
12 Sponsoring Agency Name and Address National Aeronautics and Space Administration Wallops Flight Center Wallops Island, Virginia 23337				13 Type of Report and Period Covered Contractor Report	
				14 Sponsoring Agency Code	
15 Supplementary Notes					
16 Abstract  <p>The SEAHT program is designed to process multiple passes of altimeter data with intersecting ground tracks, with the estimation of corrections for orbital errors to each pass such that the data has the best overall rms agreement at the crossover points. Orbit error for each pass is modeled as a polynomial in time, with optional orders of 0, 1, or 2. One or more passes may be constrained in the adjustment process, thus allowing passes with the best orbits to provide the overall level and orientation of the estimated sea surface heights. Intersections which disagree by more than an input edit level are not used in the error parameter estimation.</p> <p>In the program implementation, passes are grouped into South-North passes and North-South passes, with the North-South passes partitioned out for the estimation of orbit error parameters. Computer core utilization is thus dependent on the number of parameters estimated for the set of South-North arcs, but is independent on the number of North-South passes.</p> <p>Estimated corrections for each pass are applied to the data at its input data rate (normally 1/sec.) and an output tape is written which contains the corrected data.</p>					
17 Key Words (Suggested by Author(s)) GEOS-3 Altimeter Geoid			18 Distribution Statement Unclassified - unlimited  STAR Category - 61		
19 Security Classif (of this report) Unclassified		20 Security Classif (of this page) Unclassified		22 Price*	
				21 No of Pages 116	

## TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
1.0 INTRODUCTION	1
2.0 CROSSING ARC ADJUSTMENT ANALYSIS	3
2.1 FORMULATION OF CROSSOVER DIFFERENCES	3
2.2 IMPLEMENTATION CONSIDERATIONS	6
2.3 LEAST SQUARES ESTIMATION OF ORBIT IMPROVEMENT PARAMETERS	11
3.0 PROGRAM IMPLEMENTATION	17
3.1 PROGRAM ORGANIZATION	17
3.2 PROGRAM INPUT	18
3.2.1 Data Tape Input	18
3.2.2 Option Card Input	22
3.3 DATA SELECTION AND PARAMETER ESTIMATION PROCESS	36
3.4 PROGRAM OPERATION	39
3.4.1 FORTRAN Logical Units	39
3.4.2 Sample Deck Setup	40
3.5 PROGRAM OUTPUT	43
3.6 LIMITATIONS	71
4.0 PROGRAM LISTING	73
REFERENCES	116

## SECTION 1.0

### INTRODUCTION

The primary objective in the development of the SEAHT program is the improvement of sea surface height values obtained from altimeter data along intersecting arcs (i.e., arcs whose groundtracks cross). The basic concept in the improvement scheme is that, at the crossovers, the altimeter measurements are to the same point on the surface and crossover differences are due to differences in:

- orbit error
- tides
- currents
- propagation effects
- altimeter noise and bias
- eddies and other temporal sea surface height effects

Of these effects, all except orbit error can be corrected or have amplitudes below the approximately 1 m level, and the effects of measurement noise and propagation effects are expected to be reduced to near the 10 cm level. The satellite orbital height error is expected to be the dominant error source in most cases. Over short time periods (less than a quarter of a revolution), the orbit error can be modeled as a polynomial in time, and a set of orbit error parameters can be estimated such that the set of intersections are as consistent as allowed by unmodeled (or improperly modeled) temporal sea surface height

variations. In general, this orbit adjustment would be expected to be made relative to one or more passes whose orbits were known to be very good. This allows the estimated sea surface heights to be given an absolute interpretation rather than being only a set of relative heights.

Given a set of arcs, algorithms have been developed to categorize and find the intersections of altimeter passes. Algorithms are also developed for the estimation of the orbit error parameters using a Bayesian least squares technique. . .

## SECTION 2.0

### CROSSING ARC ADJUSTMENT ANALYSIS

#### 2.1 FORMULATION OF CROSSOVER DIFFERENCES

In the study of sets of intersecting arcs, it is necessary to construct matrices relating to a pass at the time that it crosses the groundtrack for another pass. This will be accomplished through double subscripts, with the first denoting the pass of interest, and the second the pass which is being intersected. E.g.,  $g_{ij}$  then refers to the  $i^{\text{th}}$  pass at the time of intersection of the groundtrack from the  $j^{\text{th}}$  pass. In all cases that will be considered, the arc lengths will be chosen sufficiently short so that the intersections are unique, and one arc does not cross another more than once.

Assuming that tide corrections have been made to altimeter sea surface height measurements, the result is the altimeter geoid measurement contaminated by, in general, orbit error. This geoid height measurement can be expressed as

$$g_{ij} = g_{ij}^* + \Delta g_{ij} + n_{ij} \quad (1)$$

where

$g_{ij}$  is the geoid height measurement

$g_{ij}^*$  is the actual geoid height

$\Delta g_{ij}$  is the error in the geoid height due to satellite height error plus any biases in the altimeter measurement

$n_{ij}$  is the error in the measurement due to noise in the altimeter measurement and to temporal sea surface height effects.

Although no analytical model is available for  $g_{ij}$ , it may be represented empirically by a polynomial in time,

$$\Delta g_{ij} = a_{i0} + a_{i1} t_{ij} + a_{i2} t_{ij}^2 + \dots + a_{iK_i} t_{ij}^{K_i} \quad (2)$$

where

$t_{ij}$  is the time along the  $i^{th}$  arc at point  $(i,j)$

Considering now the geoid height measurement at the point  $(i,j)$  along the  $j^{th}$  arc, the model equation is

$$g_{ji} = g_{ji}^* + \Delta g_{ji} + n_{ji} \quad (3)$$

But, by definition  $g_{ij}^* = g_{ji}^*$ . Therefore, using (1) and (3), we have

$$d_{ij} = g_{ij} - g_{ji} = \Delta g_{ji} - \Delta g_{ji} + n_{ij} - n_{ji}$$

where  $d_{ij}$  is the difference between the geoid height measurements at the  $(i,j)$  point. Substituting from Eqn. (2),

$$d_{ij} = \sum_{e=0}^{K_i} a_{ie} t_{ij}^e - \sum_{e=0}^{K_j} a_{je} t_{ji}^e + n_{ij} - n_{ji} \quad (4)$$

Since Equation (4) is expressed in terms of geoid height differences, a constraint must be used to anchor the solution. For a one parameter solution, one constrained revolution is sufficient. All other revolutions are adjusted such that the differences in heights between each of these and the constrained revolution will be minimized. Since orbital errors have predominantly a once per revolution type of variation, a low order polynomial should serve as a satisfactory model for short arcs. In particular, a quadratic would be expected to be the maximum required order for arc lengths not exceeding a quarter of a revolution (~25 minutes for GEOS-3) and shorter arcs should require only a first (or zero) order polynomial.

The objective is then to solve for the set of coefficients which will minimize the  $d_{ij}$ 's in some sense, subject to the constraint that certain arcs are not to be adjusted. The constraints can be applied through several different techniques. We choose the Bayesian approach since it is consistent with available software and amounts to nothing more than supplying additional measurements to the estimation scheme. The least squares technique will be chosen for the coefficient estimation. This procedure will also be minimum variance if the noise difference,  $n_{ij} - n_{ji}$ , is uncorrelated from one crossing to another and its variance is used to weight the intersection data. The degree to which the errors are uncorrelated depends primarily upon the correlation between temporal sea surface height variations but, in any case, correlation information is not expected to be available. The least squares technique then requires the minimization of

$$S = \sum_{i=1}^N \sum_{j=i+1}^N \delta_{ij} \left\{ \left( d_{ij} - \sum_{e=0}^{K-1} a_{ie} t_{ij}^e + \sum_{e=0}^{K-1} a_{je} t_{ji}^e \right)^2 w_{ij} \right\} \quad (5)$$



where

$N$  is the total number of arcs

$\delta_{ij} = 1$  if arc  $j$  intersects  $i$   
 $= 0$  if not

$w_{ij}$  = weighting factor based on  $n_{ij} - n_{ji}$   
 $= 1/E [n_{ij} - n_{ji}]^2$

with  $E$  the expected value operator. Additionally, we have assumed that

$$K_i = K_j = K-1$$

so that the number of orbit error parameters is taken to be the same for all arcs. This is not an essential assumption, but substantially simplifies the software implementation. Constraints can be used to effectively vary the number of adjusted parameters from one arc to the next.

## 2.2 IMPLEMENTATION CONSIDERATIONS

Before discussing the solution of (5) it is pertinent to consider the number of intersections required to generate a solution of a given order. First, note that the total number of intersections is

$$N_I = \sum_{i=1}^N \sum_{j=i+1}^N \delta_{ij}, \quad (6)$$

whereas the number of coefficients to be determined is

$$N_c = \sum_{i=1}^N K = NK \quad (7)$$

Obviously, for this method to be practical we must require that

$$N_I \geq N_c$$

or

$$\sum_{i=1}^N \sum_{j=i+1}^N \delta_{ij} \geq NK \quad (8)$$

In addition, we cannot solve for  $K$  coefficients along the  $i^{\text{th}}$  arc if there are fewer than  $K$  arcs intersecting arc  $i$ . Therefore, we also require

$$\sum_{j=1}^N \delta_{ij} \geq K \text{ for all } i. \quad (9)$$

In order to assess the number of arcs which it may be feasible to process in a computer, consider the case of two sets of arcs with each arc in the first set intersecting each arc in the second set. We will denote the number of arcs in the first set by  $N_a$  and the number of arcs in the second set by  $N_b$ . For a solution, we require that the number of intersections be greater than or equal to the number of coefficients, or

$$N_a N_b \geq K(N_a + N_b),$$

from which

$$N_a \geq \frac{K N_b}{N_b - K} \quad (10)$$

Minimum values of  $N_a$  for various values of  $K$  and  $N_b$  are listed in Table 1.

$K$	$N_b$	Minimum $N_a$
1	2	2
1	3	2
1	5	2
2	3	6
2	4	4
2	5	4
2	10	3
2	20	3
3	4	12
3	5	8
3	10	5
3	20	4
3	50	4

Table 1. Minimum Numbers of Crossing Arcs  
for Different Numbers of Adjusted Parameters

Note that the limiting value of  $N_a$  for large values of  $N_b$  is  $K+1$ . This can be deduced from Equation (10), since

$$\lim_{N_b \rightarrow \infty} \frac{K N_b}{N_b - K} = K \quad (11)$$

For all finite values of  $N_b$ , the ratio is greater than  $K$  so  $N_a$  must be at least  $K+1$ .

Looking now at the approximate core requirements, we consider the normal matrix to be the array which primarily limits the number of arcs which can be simultaneously processed. Allowing for this array to be double precision, but with only the diagonal and above elements stored, the number of words required for the M dimensional normal matrix is

$$N_T = \frac{M(M+1)}{2} \quad (2) = M(M+1)$$

Substituting  $M = K(N_a + N_b)$  for the number of parameters, the core required is

$$N_T = K^2(N_a + N_b)^2 + K(N_a + N_b) \quad (12)$$

Table 2 shows the core required for the normal matrix for two different relations of  $N_a$  to  $N_b$ . In one case, we set  $N_a = N_b$ , and in the other case we set  $N_b = 1$  as is appropriate for the program implementation in which the arcs in one direction are partitioned, as will be discussed in Section 2.3.

Considering the maximum core available on the Wallops computers to be on the order of 70K words, it is evident from Table 2 that the limitation on  $N_b$  for the unpartitioned solution is approximately 100 passes for a one parameter solution and approximately 50 passes for a two parameter solution. For a partitioned solution, these limits are almost doubled, allowing approximately 200 one parameter arcs or 100 two parameter arcs.

K	$N_a$	$N_T$	
		$N_b = N_a$	$N_b = 1$
1	2	20	12
	5	110	42
	10	420	132
	20	1640	462
	50	10100	2652
	100	40200	10302
	150	90300	22952
	200	160400	40602
2	4	272	110
	10	1640	506
	20	6480	1806
	50	40200	10506
	100	160400	41006
3	6	1332	462
	10	3660	1122
	20	14520	4032
	50	90300	23562
	100	360600	92112

Table 2. Normal Matrix Storage Requirements  
for Different Numbers of Arcs and Parameters Per Arc

## 2.3 LEAST SQUARES ESTIMATION OF ORBIT IMPROVEMENT PARAMETERS

The least squares estimate of the parameters which minimize the altimeter crossovers is obtained by finding the set of  $a$ 's which minimize the sum of squares of crossover differences given by Equation (5). Equivalently, we can consider the least squares solution of the set of linear equations given by Equation (4), which may be written symbolically in matrix form as

$$\mathbf{Y} = \mathbf{B}\mathbf{Z} + \bar{\mathbf{e}} \quad (13)$$

where

$\mathbf{Y}$  is the vector of geoid height differences.

$\mathbf{B}$  is the matrix of partial derivatives of the geoid height differences with respect to the orbit error parameters. This matrix will consist of powers of time from some reference time for each pass.

$\mathbf{Z}$  is the vector of orbit error coefficients to be solved for.

$\bar{\mathbf{e}}$  is the vector of errors in the crossover differences due to measurement noise.

Table 3 shows Equation (13) written out explicitly for a two coefficient parameterization of orbit error and 4 North-South passes crossing 4 South-North passes.\* For convenience, the

---

\*The solution of the set of equations given in Table 3 is actually singular. Intuitively, it is obvious that whatever solution is obtained for the  $a_{j0}$ 's, the same constant added to each of these coefficients is an equally valid solution. The solution can be made non-singular through the use of a constraint on one or more of the passes. We will assume that such information is to be used, but will not explicitly include it in the equations shown here.

Table 3. Matrix Form of Linear Equations to be Solved for  
4 Passes Crossing 4 Passes in the Opposite Direction and  
2 Orbit Parameters Per Pass

12

$$\begin{bmatrix} d_{15} \\ d_{16} \\ d_{17} \\ d_{18} \\ d_{25} \\ d_{26} \\ d_{27} \\ d_{28} \\ d_{35} \\ d_{36} \\ d_{37} \\ d_{38} \\ d_{45} \\ d_{46} \\ d_{47} \\ d_{48} \end{bmatrix} = \begin{bmatrix} 1 & t_{15} & 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{51} & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & t_{16} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{61} & 0 & 0 & 0 & 0 \\ 1 & t_{17} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{71} & 0 & 0 \\ 1 & t_{18} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{81} \\ 0 & 0 & 1 & t_{25} & 0 & 0 & 0 & 0 & -1 & -t_{52} & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & t_{26} & 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{62} & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & t_{27} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{72} & 0 & 0 \\ 0 & 0 & 1 & t_{28} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{82} \\ 0 & 0 & 0 & 0 & 1 & t_{35} & 0 & 0 & -1 & -t_{53} & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & t_{36} & 0 & 0 & 0 & 0 & -1 & -t_{63} & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & t_{37} & 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{73} & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & t_{38} & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{83} \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & t_{45} & -1 & -t_{54} & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & t_{46} & 0 & 0 & -1 & -t_{64} & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & t_{47} & 0 & 0 & 0 & 0 & -1 & -t_{74} & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & t_{48} & 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{84} \end{bmatrix} \begin{bmatrix} a_{10} \\ a_{11} \\ a_{20} \\ a_{21} \\ a_{30} \\ a_{31} \\ a_{40} \\ a_{41} \\ a_{50} \\ a_{51} \\ a_{60} \\ a_{61} \\ a_{70} \\ a_{71} \\ a_{80} \\ a_{81} \end{bmatrix} + \begin{bmatrix} n_{15}-n_{51} \\ n_{16}-n_{61} \\ n_{17}-n_{71} \\ n_{18}-n_{81} \\ n_{25}-n_{52} \\ n_{26}-n_{62} \\ n_{27}-n_{72} \\ n_{28}-n_{82} \\ n_{35}-n_{53} \\ n_{36}-n_{63} \\ n_{37}-n_{73} \\ n_{38}-n_{83} \\ n_{45}-n_{54} \\ n_{46}-n_{64} \\ n_{47}-n_{74} \\ n_{48}-n_{84} \end{bmatrix}$$

North-South arcs have been denoted as arcs 1-4 and the South-North passes as arcs 5-8.

The weighted least squares solution of Equation (13) is [1]

$$\hat{Z} = (B^T W B)^{-1} B^T W \bar{Y} \quad (14)$$

where

$\hat{Z}$  is the estimated set of coefficients

$W^{-1} = E[\bar{\epsilon} \bar{\epsilon}^T] = \text{covariance of the measurement noise,}$   
with  $E$  the expectation operator.

That the solution allows partitioning can be seen by rewriting the equations given in Table 3 in the form:

$$\begin{bmatrix} Y_1 \\ Y_2 \\ Y_3 \\ Y_4 \end{bmatrix} = \begin{bmatrix} B_1 & 0 & 0 & 0 & B_{10} \\ 0 & B_1 & 0 & 0 & B_{20} \\ 0 & 0 & B_3 & 0 & B_{30} \\ 0 & 0 & 0 & B_4 & B_{40} \end{bmatrix} \begin{bmatrix} a_1 \\ a_2 \\ a_3 \\ a_4 \\ a_0 \end{bmatrix} + \begin{bmatrix} n_1 \\ n_2 \\ n_3 \\ n_4 \end{bmatrix} \quad (15)$$

where

$$Y_i = \begin{bmatrix} d_{i5} \\ d_{i6} \\ d_{i7} \\ d_{i8} \end{bmatrix}$$

ORIGINAL PAGE IS  
OF POOR QUALITY



$$B_i = \begin{bmatrix} 1 & t_{i5} \\ 1 & t_{i6} \\ 1 & t_{i7} \\ 1 & t_{i8} \end{bmatrix}$$

$$B_{i0} = \begin{bmatrix} -1 & -t_{5i} & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & -1 & -t_{6i} & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & -1 & -t_{7i} & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & -1 & -t_{8i} \end{bmatrix}$$

$$a_i = \begin{bmatrix} a_{i0} \\ a_{i1} \end{bmatrix}$$

$$a_0 = \begin{bmatrix} a_{50} \\ a_{51} \\ a_{60} \\ a_{61} \\ a_{70} \\ a_{71} \\ a_{80} \\ a_{81} \end{bmatrix}$$

$$n_i = \begin{bmatrix} n_{i5} - n_{5i} \\ n_{i6} - n_{6i} \\ n_{i7} - n_{7i} \\ n_{i8} - n_{8i} \end{bmatrix}$$

Assuming only that the  $n_i$ 's are uncorrelated, and denoting

$$W_i^{-1} = E[n_i n_i^T], \quad (16)$$

Equation (14) for the 8 arc 16 parameter case of Table 3 becomes

$$\begin{bmatrix} \hat{a}_1 \\ \hat{a}_2 \\ \hat{a}_3 \\ \hat{a}_4 \\ \hat{a}_0 \end{bmatrix} = \begin{bmatrix} B_1^T W_1 B_1 & 0 & 0 & 0 & B_1^T W_1 B_{10} \\ 0 & B_2^T W_2 B_2 & 0 & 0 & B_2^T W_2 B_{20} \\ 0 & 0 & B_3^T W_3 B_3 & 0 & B_3^T W_3 B_{30} \\ 0 & 0 & 0 & B_4^T W_4 B_4 & B_4^T W_4 B_{40} \\ (B_1^T W_1 B_{10})^T & (B_2^T W_2 B_{20})^T & (B_3^T W_3 B_{30})^T & (B_4^T W_4 B_{40})^T & \sum_{i=1}^4 B_{i0}^T W_i B_{i0} \end{bmatrix}^{-1} \times \begin{bmatrix} B_1^T W_1 Y_1 \\ B_2^T W_2 Y_2 \\ B_3^T W_3 Y_3 \\ B_4^T W_4 Y_4 \\ \sum_{i=1}^4 B_{i0}^T W_i Y_i \end{bmatrix} \quad (17)$$

The matrix inverse in Equation (17) can be obtained via partitioning [1] with the resulting expressions for the coefficient sets found to be

$$\hat{a}_0 = M_0 \sum_{i=1}^4 [B_{i0}^T W_i Y_i - B_{i0}^T W_i B_i (B_i^T W_i B_i)^{-1} B_i^T W_i Y_i] \quad (18)$$

ORIGINAL PAGE IS  
OF POOR QUALITY

$$\hat{a}_i = (B_i^T W_i B_i)^{-1} B_i^T W_i Y_i - (B_i^T W_i B_i)^{-1} B_i^T W_i B_{i0} \hat{a}_0 \quad (19)$$

where

$$M_0^{-1} = \sum_{i=1}^4 [B_{i0}^T W_i B_{i0} - B_{i0}^T W_i B_i (B_i^T W_i B_i)^{-1} (B_{i0}^T W_i B_i)^T] \quad (20)$$

The extension of the solution given by Equations (18-20) to any number of arcs is achieved through two directions. Let us refer to the arcs for which the  $a_i$  parameters have been assigned as North-South arcs, and the set of arcs for which the  $a_0$  set of parameters have been assigned as South-North arcs. To increase the number of North-South arcs, we simply increase the summation limit in Equations (18) and (10). To increase the number of South-North arcs, we must increase the number of  $a_0$  parameters and thus the size of  $M_0$  which is, in general, the matrix providing the major limitation on the number of passes which can be processed in one computer run.

The estimation scheme implemented in SEAHT is the partitioned least squares type solution described above, with the number of adjustable parameters per pass selectable as 1, 2, or 3. North-South arcs are partitioned out, so virtually any number of North-South passes can be processed simultaneously. South-North arcs provide the "common" parameter set, and the number of such passes is limited by available computer core.

## SECTION 3.0 PROGRAM IMPLEMENTATION

### 3.1 PROGRAM ORGANIZATION

The SEAHT program utilizes overlays, and consists primarily of a main program (plus common block initialization), an input set of routines, and an estimation set of routines. The last set of routines, however, is divided into two groups, and there is an additional segment used for core allocation. Thus, there are a total of four program "LINKS" plus a main program segment.

The main program is responsible for the flow of the program, and for the computation of necessary array sizes. In LINK 1, optional input is read from cards and input data is read from tape(s), and the arc crossings are computed. The crossing data is stored on disk in the form to be used by the estimation routines. The order of the crossings is: all crossings of the first North-South arc, followed by all crossings of the second North-South arc, etc. This format allows the partitioning scheme discussed above to be implemented. LINK 1 contains routines with fixed array sizes, with dimensions set to accommodate the maximum amounts of data per arc and maximum number of arcs that are expected. However, these dimensions do not result in excessive core utilization.

At the conclusion of the computation of the arc crossings, the needed sizes for all arrays in the estimation process are calculated by the main program. LINK 1 is then overlaid by LINK 2 which contains a portion of the estimation routines. LINK 3 is then called to perform dynamic memory allocation for all arrays needed in the parameter estimation process. After this allocation, LINK 3 is overlaid by LINK 4 containing

the remainder of the estimation routines. No further overlays are performed.

Control of the estimation process is from subroutine SOLVE, which is responsible for controlling the normal matrix set-up, the application of constraints, the parameter adjustments, and the application of the estimated parameters to the input data, with the corrected data then saved on tape.

### 3.2 PROGRAM INPUT

Input to the SEAHT program consists of one or more data tapes, and card input which requests certain program options. The latter category consists of a set of option cards, at least one of which is required.

#### 3.2.1 Data Tape Input

Data input files to SEAHT consist of a header record followed by a set of data records, as specified on the following two pages. The header record identifies the time of the data by both the revolution (and segment) number and date. At the present time, the date is not used, while the revolution and segments numbers are used for the selection and deletion of particular data passes, as discussed below.

Input tapes may be prepared in several different ways. They may be prepared by extracting information contained on each frame of an ARC [2] tape, in which case sea surface heights are major frame ( $\sim 2.0$  or  $3.2$  seconds) averages. In addition, the ALTKAL program [3] produces a tape which is directly readable by SEAHT. This tape contains smoothed sea surface heights at the 1/second data rate.

In the current program implementation, only Words 1-5 of the header record and Words 1-4 of the data record are read by SEAHT, and the first 3 words of the header record are not used. Words 4-5 of the header record and the first 4 words of each data record are critical to program operation.

ORIGINAL PAGE IS  
OF POOR QUALITY

SEAHT Input Format  
Header Record

<u>Word No.</u>	<u>Type</u>	<u>Description</u>
1	I	Year and Day of year (YYDDD)
2-3	DP	Time of day (seconds) for first data record
4	I	Segment number for altimeter data pass
5	I	Rev number for altimeter data pass
6	I	Measurement type 40 = Global mode 41 = Intensive mode
7-19	I	Zeroes (used for making all records same length)

SEAHT Input Format  
Data Record

<u>Word No.</u>	<u>Type</u>	<u>Description</u>
1	R	Time from first data point (minutes)
2	R(LAT)	Latitude of sea surface height
3	R(LON)	Longitude of sea surface height
4	R	Sea surface height (meters)
5-13	R	Not used. (For tapes created by the ALTKAL smoother, words 4-13 contain sea surface heights at the 10/sec data rate.)
14	R(THITE)	Tide height (meters)
15	R(TREF)	Tropospheric refraction correction (meters)
16	R(RAGCAV)	Average AGC
17-19	R	Zeroes for future additions

Note: The "sea surface height" value(s) have been corrected using the tropospheric refraction correction and tide height on the data record. Strictly speaking, the sea surface height is the altimeter measurement of geoid height, although including the effects of currents and other non-stationary sea surface height effects.



### 3.2.2 Option Card Input

Through the use of one or more of nine different keyword option cards, various aspects of the operation of SEAHT can be altered from the default mode. These option cards and the purpose for which they are utilized are

- AREA - defines the geographic area for which arc crossings are to be selected.
- PARAM - selects the number of coefficients to be used for each pass to parametrize orbit error.
- NODATA - specifies that arc crossings have been saved from a previous program execution and are to be input in place of the normal data tapes.
- CONSTR - specifies that a particular pass is to be treated as having a good orbit with the parameters constrained in the adjustment process.
- EDIT - specifies the level at which arc crossing differences are to be edited from the parameter estimation.
- SELECT - specifies that only particular passes are to be selected from a particular data tape.
- DELETE - specifies that all passes are to be selected from a particular tape except for those which are designated.

## AREA

AREA	55.0	67.0	300.0	250.0
000000	000000	000000	000000	000000
1 2 3 4 5 6	7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25	26 27 28 29 30 31 32 33 34 35 36 37 38 39 40	41 42 43 44 45 46 47 48 49 50 51 52 53 54 55	56 57 58 59 60 61 62 63 64 65 66 67 68 69 70
11	1111111111111111	1111111111111111	1111111111111111	1111111111111111
222222	2222222222222222	2222222222222222	2222222222222222	2222222222222222
333333	333333 33333333	333333 33333333	3333 33 33333333	3333 3 33333333
444444	4444444444444444	4444444444444444	4444444444444444	4444444444444444
55	5555555555 5555555555	5555555555555555	5555555555555555	5555555555555555
666666	6666666666666666	6666 666666666666	6666666666666666	6666666666666666
777777	7777777777777777	77777 7777777777	7777777777777777	7777777777777777
888888	8888888888888888	888888 8888888888	8888888 88888888	88888888 88888888
9	9999999999999999	9999999999999999	9999999999999999	9999999999999999
1 2 3 4 5 6	7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25	26 27 28 29 30 31 32 33 34 35 36 37 38 39 40	41 42 43 44 45 46 47 48 49 50 51 52 53 54 55	56 57 58 59 60 61 62 63 64 65 66 67 68 69 70

<u>NAME</u>	<u>COLUMNS</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
AREA	1-4	A4	Defines the area of interest
	11-25	E15.5	Minimum acceptable value of latitude
	26-40	E15.5	Maximum acceptable value of latitude
	41-55	E15.5	Minimum acceptable value of longitude
	56-70	E15.5	Maximum acceptable value of longitude

IF CARD OMITTED: Default values are: minimum latitude, -90.0 degrees;  
maximum latitude, +90.0 degrees; minimum  
longitude, 0.0 degrees; maximum longitude,  
-360.0 degrees.

ORIGINAL PAGE IS  
OF POOR QUALITY

2

MECC-5081

parameters for each pass.

NODATA

[illegible]

<u>NAME</u>	<u>COLUMNS</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
NODATA	1-6	A6	Indicates crossing data already exists
	7-10	I4	The logical unit number of the disk or tape where the crossing data is stored

ORIGINAL PAGE IS  
OF POOR QUALITY

## CONSTR

[illegible]

<u>NAME</u>	<u>COLUMNS</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
CONSTR	1-6	A6	Constrains selected revs (other revs are adjusted to fit constrained rev and constrained revs are not adjusted)
	7-10	I4	Type of constraint = 1, pass totally constrained (bias, slope and curvature) = 2, bias adjusted, slope and curvature constrained = 3, bias and slope adjusted, curvature constrained
	11-25	E15.6	Number of a revolution to be constrained

CONSTR  
(Cont.)

<u>NAME</u>	<u>COLUMNS</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
CONSTR (Cont.)	26-40	E15.6	Segment number associated with the rev number in columns 11-55

Note: The use of a constraint is meaningless unless the parameter has been otherwise requested to be adjusted. E.g., the constraint of curvature for a pass is meaningless if only bias and slope are being adjusted, and should therefore not be requested.

ORIGINAL PAGE IS  
OF POOR QUALITY

## EDIT

[illegible]

<u>NAME</u>	<u>COLUMNS</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
EDIT	1-4__	A4	Sets editing criteria.
	11-25	E15.6	Maximum acceptable difference in sea surface heights at any crossing point (meters).

IF CARD OMITTED: Default value is 100.0 meters.

## DATA

[illegible]

<u>NAME</u>	<u>COLUMNS</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
DATA	1-4	A4	Indicates the source of the data to be read in
	7-10	I4	Logical unit from which data is to be read
	11-25	E15.6	Number of files to be read from the logical unit designated in columns 7-10

As many as six of these cards are possible barring limitations set outside the program.

ORIGINAL PAGE IS  
OF POOR QUALITY



## SELECT

[illegible]

<u>NAME</u>	<u>COLUMNS</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
SELECT	1-6	A6	Selects revolutions from a specific tape
	7-10	I4	Logical unit number of the tape from which selection is to be made
	11-25	E15.6	Revolution to be selected
	26-40	E15.6	Segment number associated with revolution designated in Columns 11-25
	41-55	E15.6	Revolution to be selected*

\* If not more than one revolution is selected, columns 41-80 should be blank.

SELECT (cont.)

<u>NAME</u>	<u>COLUMN</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
	56-70	E15.6	Segment number associated with the revolution designated in columns 41-55.

LIMITATION: Multiple SELECT cards are permitted, but no more than 50 selections may be made from the same logical unit number.

ORIGINAL PAGE IS  
OF POOR QUALITY

DELETE

DELETE 21										4227.										156.									
0000 00																													

<u>NAME</u>	<u>COLUMNS</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
DELETE	1-6	A6	Deletes revolutions not desired from a specific tape
	7-10	I4	Logical unit number of the tape from which deletion is to be made
	11-25	E15.6	Revolution to be deleted
	26-40	E15.6	Segment number associated with the revolution in columns
	41-55	E15.6	Revolution to be deleted*

\* If not more than one revolution is deleted columns 41-80 should be blank.

## DELETE

<u>NAME</u>	<u>COLUMN</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
	56-70	E15.6	Segment number associated with the revolution designated in columns 41-55

LIMITATION: Multiple DELETE cards are permitted, but no more than 50 deletions may be made from the same logical unit number.

ORIGINAL PAGE IS  
OF POOR QUALITY

ZERO

[illegible]

<u>NAME</u>	<u>COLUMNS</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
ZERO	1-4	A4	Sets a longitude different than Greenwich as the longitude origin.
	11-25	E15.6	Longitude, relative to Greenwich, to be used as origin.

PURPOSE: Since the method of finding intersections of revolutions is dependent upon a decreasing longitude in the area of interest, it may be necessary to, temporarily, zero-set a certain longitude in the area of least interest. This is done within the program and requires no additional computation by the user.

MINUTE

[illegible]

<u>NAME</u>	<u>COLUMNS</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
MINUTE	1-6	A6	Permits the time to be input in minutes

IF CARD OMITTED: The units of time are assumed to be in days and are changed to minutes within the program.

ORIGINAL PAGE IS  
OF POOR QUALITY

### 3.3 DATA SELECTION AND PARAMETER ESTIMATION PROCESS

The estimation process begins with the acceptance of data that was collected in the area of interest. The revolutions are classified as being north-south or south-north. A revolution whose latitude increases to the maximum possible value (approximately  $65^{\circ}$ ) and, then, decreases is separated into a south-north segment and a north-south segment. This also applies to revolutions whose latitude decreases to the minimum value (approximately  $-65^{\circ}$ ) and, then, increases.

Preliminary to finding crossing points, tests are made based on the fact that there will not be an intersection if the exiting latitude of a south-north revolution is less than the exiting latitude of the north-south revolution or if the entering latitude of the north-south revolution is less than the entering latitude of the south-north revolution. If the exiting longitude of the north-south revolution is greater than the entering longitude of the south-north revolution or the exiting longitude of the south-north revolution is greater than the entering longitude of the north-south revolution, there will not be a crossing.

Every south-north revolution is compared to every north-south revolution to determine crossing points by the following method:

1. Equations for lines connecting the entering and exiting points of the revolutions are determined, and the intersections of these lines computed.

2. The latitudes, corresponding to the longitude at the intersection, are found for each revolution, and the difference between these values is computed. If the absolute value of this difference is less than .0001 degrees, the average of the latitudes is taken, and a crossing point is declared at this average latitude and the longitude corresponding to the intersection point of the lines connecting entering and exiting points of the revolutions.
3. If the difference is too great and the latitude is larger for the north-south revolution, these points become the entering points of the revolutions. Otherwise, they become the exiting points. This process continues until a crossing point is found or the number of iterations exceeds ten.

The times into the revolutions and the sea surface heights at these crossing points are found by interpolation.

A process to determine whether each revolution has crossed other revolutions a sufficient number of times is performed. The process repeatedly deletes revolutions and checks for sufficient crossings until it is not necessary to delete any additional revolutions.

Examining one crossing point at a time, the difference in sea surface heights (sea surface height of the north-south revolution minus the sea surface height of the south-north revolution) at the crossing point is computed as well as the powers of time along the revolutions at this crossing point. The elements of the normal matrix  $B^T W B$  are computed and placed in their appropriate position as are the elements of the  $B^T W Y$  matrix. The noise on each revolution is assumed to be the same.



Next, the north-south revolutions which are to be constrained are noted and elements of the  $B^T_{WB}$  matrix are altered to ensure that the coefficients of the bias for this revolution will be small and that adjustments on other revolutions will, necessarily, be made relative to this revolution.

Handling all crossing point data for one north-south revolution at a time, inversion of the normal matrix is performed and biases are computed for the north-south revolutions based on the information from each particular north-south revolution under consideration with the south-north passes held fixed. After all the north-south passes have been processed, the south-north constraints (if any) are applied and the normal matrix for the south-north passes is calculated (Eqn. 20). The south-north biases are then computed (Eqn. 18) and the north-south biases updated (Eqn. 19).

. All data are corrected for the biases found.

### 3.4 PROGRAM OPERATION

A source deck and binary decks of SEAHT are located at the Wolf Research and Development Group office in Pocomoke City, Maryland. The Honeywell 625/635 run setup consists of the appropriate control cards, the program on binary cards, the desired data cards, and a source of data input. The standard setup for a run consists of the following:

- Specification of the FORTRAN FILE units for both the disk files used by the program and the tapes used for data input.
- Program binary deck.
- The set of option cards required for the particular run.

A sample job setup is given in Section 3.4.2.

#### 3.4.1 FORTRAN Logical Units

In addition to the normal card input and printer output files, SEAHT uses 5 scratch files, writes one output tape, writes 2 additional printer files, and normally uses 1-6 input tapes. All scratch files are sequentially accessed and logically could also be assigned to tapes. However, some of the files - particularly unit 12 - are rewound a number of times and could lead to inefficient program operation if assigned to tape.

The FORTRAN logical units used are as follows:

ORIGINAL PAGE IS  
OF POOR QUALITY

LOGICAL  
UNIT

USE

5	Option card input
6	Standard printer output
10	Output tape of corrected data
11	Disk storage during execution
12	Disk storage during execution
13	Disk storage during execution
14	Disk storage during execution
15	Disk storage during execution
18	Printed output
19	Printed output
*	Input tapes (normally multi-file)

\*This set must be comprised of unique numbers different from the other units listed above. Multi-file tapes must be non-standard label. Single file tapes may be either standard label or non-standard label. A total of up to 6 input tapes may be used in a job.

#### 3.4.2 Sample Deck Setup

The following is an example of a working deck setup. This particular setup would require that nineteen files be read from the tape with logical unit number 21 (in this case, tape #4572). A height bias would be found for all passes within the area: latitude; 45°-60°, longitude; 285°-300°, which are found to cross another pass. Rev 4476, segment 169 would not be adjusted and the biases determined for the other passes would be relative to this constrained pass.

COL.

<u>1</u>	<u>8</u>	<u>16</u>	
\$	IDENT	112293,SEAHT	
\$	OPTION	FORTRAN	
	.		
	.		
	.		
\$	LINK	LINK1	
	.		
	.		
	.		
\$	LINK	LINK2, LINK1	
	.		
	.		
	.		
\$	LINK	LINK3	
	.		
	.		
	.		
\$	LINK	LINK4, LINK3	
	.		
	.		
	.		
\$	EXECUTE	DUMP	
\$	LIMITS	20,47K,10K	
\$	TAPE9	10,X6D,,,WJTAPE	
\$	FFILE	10,NSTD LB,NOSRLS, FIXLNG/5,BUFS1Z/5,MLTFIL	
\$	TAPE	21,X2D,,4572	
\$	FFILE	21,NSTD LB,NOSRLS, FIXLNG/10,BUFS1Z/320,MLTFIL	

PROGRAM  
BINARY  
DECK

ORIGINAL PAGE IS  
OF POOR QUALITY

COL.

<u>1</u>	<u>8</u>	<u>16</u>	<u>30</u>	<u>45</u>	<u>60</u>
\$	FILE	11,D1R,50S			
\$	FILE	12,D2R,50S			
\$	FILE	13,D3R,50S			
\$	FILE	14,D4R,50S			
\$	FILE	15,D5R,50S			
\$	FILE	H*,F6R,144R			
\$	SYSOUT	18			
\$	SYSOUT	19			
\$	INCODE	IBMF			
DATA	21	19.			
PARAM	01				
CONSTR	01 ,	4476.	169.		
AREA		21.	45.	270.	315.
\$	ENDJOB				

### 3.5 PROGRAM OUTPUT

The program output which would result from the setup described in Section 3.4.2 has been reproduced on the following pages. The printed output shows the area and the number of parameters used (Table 4). A tally of rev types and a list of revs for each type is printed (Table 5). The revs which were constrained are printed in Table 6. Tables 7 and 8 differ only when passes are edited because an insufficient number of crossings exists to solve for the requested set of parameters for each pass. E.g., it is not possible to estimate both bias and slope parameters for a pass with only one crossing, and the pass is accordingly deleted. The allocation of memory for matrices and their starting addresses are shown in Table 9. Table 10 shows the biases found (note that Rev 4476/Seg. 169 was constrained). Tables 11 and 12 show the corrections made at the crossing points (respective of the north-to-south in Table 11 and the south-to-north in Table 12).

Additional output has been included to show the effect that passes reaching maximum latitude have on the program; i.e., how the program handles passes that can be typed in more than one way (Tables 13-21).

The data which is corrected and output on 9-track tape, readable by the ECLIPSE S200, is described in Table 22.

ORIGINAL PAGE IS  
OF POOR QUALITY

# SEAHT

LEAST SQUARES DETERMINATION OF SMOOTHED SEA SURFACE HEIGHTS  
CALCULATED AT INTERSECTING POINTS OF CROSSING REVOLUTIONS

CALIBRATION AREA  
LATITUDE 25.00 TO 45.00  
LONGITUDE 270.00 TO 315.00

NO. OF PARAMETERS = 1

NO. OF SOUTH-TO-NORTH REVS = 7

NO. OF NORTH-TO-SOUTH REVS = 12

44.

TABLE 4

NORTH-TO-SOUTH REVOLUTIONS

REV NO	SEG NO
4476	169
4334	82
4604	249
4462	160
4391	117
1974	294
1576	462
2102	387
1178	104
3552	879
1718	81
1988	303

SOUTH-TO-NORTH REVOLUTIONS

REV NO	SEG NO
4610	255
4624	278
4482	175
4553	218
2094	382
1710	73
2151	422

TABLE 5

ORIGINAL PAGE IS  
OF POOR QUALITY



..

\*\*\*\*\*CONSTRAINED REVS\*\*\*\*\*

REV NO.	SEG. NO.	TYPE OF CONSTRAINT		
		HEIGHT	SLOPE	CURVATURE
4476	169			*

TABLE 6

# ARC CROSSING DATA INPUT FOR THIS RUN

REVOLUTION NO				CROSSING POINTS		SMOOTHED SEA		SURFACE HEIGHT		TIME FROM EPOCH	
NORTH-SOUTH	SOUTH-NORTH	SOUTH-NORTH		LATITUDE	LONGITUDE	NORTH-SOUTH	SOUTH-NORTH	NORTH-SOUTH	SOUTH-NORTH	NORTH-SOUTH	SOUTH-NORTH
(REV/SEG)	(REV/SEG)	(REV/SEG)		(DEGREES)	(DEGREES)	(METERS)	(METERS)	(MINUTES)	(MINUTES)	(MINUTES)	(MINUTES)
4476	169	4510	255	32.45963	291.84935	-53.41363	-53.21657	2144.82202	2094.13519		
4476	169	4524	278	35.89903	294.58523	-44.48449	-44.83744	214.90916	2053.33249		
4476	169	4482	175	33.33520	292.52428	-51.29345	-51.48305	1732.18018	2144.07568		
4476	169	4553	218	34.63855	293.55638	-47.98283	-48.35899	1115.11148	1714.92035		
4476	169	2094	382	27.67230	288.38274	-58.62893	-57.23110	4378.14001	2002.44388		
4476	169	1710	73	30.58033	290.44606	-58.16207	-57.57306	3025.93799	1970.30901		
4334	82	4510	255	35.07880	289.78633	-51.44165	-51.51245	1882.11766	3329.28116		
4334	82	4524	278	38.29404	292.52493	-46.23445	-46.01506	340.31153	3200.98703		
4334	82	4492	175	35.89852	290.46118	-49.84351	-49.84628	1491.41762	3357.28058		
4334	82	4353	218	37.11724	291.49323	-48.38054	-48.47816	907.62082	2895.14792		
4334	82	1710	73	33.31563	288.38353	-56.32589	-56.58433	2717.12689	3249.20496		
4604	249	4510	255	33.33507	291.17394	-52.53151	-53.07022	1783.27779	2505.90063		
4604	249	4624	278	36.70143	293.91276	-45.11979	-45.46606	182.41389	2436.21045		
4604	249	4482	175	34.19322	291.84682	-50.79486	-51.44217	1377.85480	2548.61484		
4604	249	4553	218	35.46303	292.88094	-47.71143	-48.47261	771.75292	2108.57404		
4604	249	2094	382	28.64370	287.70745	-55.68188	-55.99393	3979.45212	2450.49774		
4604	249	1710	73	31.49521	289.77079	-56.72089	-57.42927	2649.26337	2396.45407		
4604	249	2151	422	26.14844	285.99549	-50.69884	-51.54139	5133.90637	2391.24704		
4462	160	4553	218	37.89196	290.81810	-47.82329	-48.18358	535.48232	3267.14432		
4391	117	4482	175	37.89222	288.75386	-48.02431	-48.74884	532.98451	4311.45142		
1974	294	4610	255	33.37986	291.13981	-52.75601	-53.10049	1688.78401	2526.51672		
1974	294	4624	278	36.74193	293.87828	-45.17331	-45.43630	91.68554	2455.56882		
1974	294	4482	175	34.23519	291.81462	-50.86588	-51.42990	1284.28571	2568.91663		
1974	294	4553	218	35.51037	292.84657	-48.20100	-48.53621	679.60391	2128.40247		
1974	294	2094	382	28.69168	287.67375	-55.64155	-56.03182	3880.30493	2472.67120		
1974	294	1710	73	31.54072	289.73684	-56.99466	-57.48225	2552.85614	2417.68823		
1974	294	2151	422	26.19841	285.96199	-51.02344	-51.39341	5032.57422	2414.17776		
1976	462	4610	255	34.23416	290.46656	-52.99675	-53.02664	1202.31419	2929.42444		
1976	462	4482	175	35.07230	291.14130	-51.52079	-51.52854	805.12060	2964.67441		
1976	462	4553	218	36.31880	292.17323	-48.26258	-49.19711	211.50903	2513.41693		
1976	462	2094	382	29.64004	287.00087	-55.10346	-55.01818	3356.01572	2911.67218		
1976	462	1710	73	32.43319	289.06383	-56.91784	-56.98485	2051.03781	2834.84293		
1976	462	2151	422	27.19248	285.28925	-50.34713	-50.47452	4489.88635	2871.02502		
2102	387	4610	255	34.25205	290.45231	-52.33857	-52.98447	1478.91104	2937.87918		
2102	387	4482	175	35.08976	291.12711	-50.66233	-51.48080	1081.68381	2972.95511		
2102	387	4553	218	36.33569	292.15907	-48.16755	-49.26047	488.02897	2521.43231		
2102	387	2094	382	29.66020	286.98638	-55.05340	-55.05228	3632.77325	2921.04388		
2102	387	1710	73	32.45202	289.04948	-56.81059	-56.96498	2327.69366	2843.66019		
2102	387	2151	422	27.21384	285.27465	-51.23919	-50.52425	4766.73920	2880.85709		
1178	104	4610	255	35.05774	289.80349	-51.47779	-51.57277	1606.56949	3319.29059		

TABLE 7

1178	104	4024	278	38,27530	202,54158	-46,46430	-46,03265	67,42700	3191,98083
1178	104	4482	175	35,87807	290,47823	-50,02304	-49,83742	1216,52719	3347,54004
1178	104	4553	218	37,09769	291,51006	-48,14527	-48,50958	633,73615	2885,77856
1178	104	2094	332	30,55528	286,33811	-54,91659	-54,98199	3723,01672	3337,09067
1178	104	1710	73	33,29426	288,40095	-55,91979	-56,59882	2440,21732	3238,70004
1178	104	2151	422	28,15411	284,62661	-51,34346	-51,75623	4838,60590	3314,17050
3552	879	4610	255	33,39451	291,12839	-46,94230	-53,11638	1844,67471	2533,40982
3552	879	4624	278	36,75532	293,86686	-41,20212	-45,43241	246,14857	2461,97546
3552	879	4482	175	34,25052	291,80320	-45,19866	-51,43007	1439,82391	2575,68604
3552	879	4553	218	35,52424	292,83718	-43,01505	-48,55303	834,60037	2134,99152
3552	879	2094	332	28,70793	287,66233	-46,75507	-56,04250	4038,01172	2480,18259
3552	879	1710	73	31,55601	289,72942	-49,95370	-57,49687	2709,48355	2424,82361
3552	879	2151	422	26,21544	285,95657	-40,58103	-51,34337	5191,16931	2421,99570
1718	81	4110	255	31,57794	292,51498	-52,79746	-52,65171	1672,58382	1681,29201
1718	81	4124	278	35,09123	295,25341	-44,53096	-45,06153	16,48501	1669,41060
1718	81	4482	175	32,47186	293,18975	-50,64760	-50,70387	1253,44106	1738,45343
1718	81	4553	218	33,80306	294,22169	-47,88057	-48,04806	626,49030	1320,18997
1718	81	2094	332	26,69729	289,04887	-58,22546	-58,05201	3939,24167	1553,52240
1718	81	1710	73	29,66031	291,11182	-57,16647	-57,30741	2567,31482	1543,11702
1718	81	2151	422	24,11172	287,33712	-52,86048	-52,86401	5127,53009	1458,96642
1988	303	4610	255	29,71754	293,87719	-52,42044	-52,65150	1959,16600	814,55627
1988	303	4624	278	33,38137	296,61583	-44,07055	-44,16325	243,44985	861,44814
1988	303	4482	175	30,64354	294,55204	-50,80455	-51,70658	1525,30772	886,32440
1988	303	4553	218	32,03656	295,58401	-44,49924	-44,72337	875,87438	490,18060
1988	303	2094	332	24,64896	290,41068	-58,42932	-58,69779	4300,31201	614,65333
1988	303	1710	73	27,72266	292,47371	-55,49784	-55,92331	2884,51242	647,50870
1988	303	2151	422	21,97517	288,69878	-53,67839	-54,06509	5523,58356	485,65553

TABLE 7 (Cont.)

# ARC CROSSING DATA USED FOR ADJUSTMENTS

REVOLUTION NO				CROSSING POINTS		SMOOTHED SEA SURFACE HEIGHT		TIME FROM EPOCH	
NORTH-SOUTH	SOUTH-NORTH	NORTH-SOUTH	SOUTH-NORTH	LATITUDE	LONGITUDE	NORTH-SOUTH	SOUTH-NORTH	NORTH-SOUTH	SOUTH-NORTH
(REV/SEG)	(REV/SEG)	(REV/SEG)	(REV/SEG)	(DEGREES)	(DEGREES)	(METERS)	(METERS)	(MINUTES)	(MINUTES)
4476	169	4610	255	32.45966	291.84935	-53.41368	-53.21657	2144.82202	2094.13519
4476	169	4624	278	35.89903	294.58823	-44.48449	-44.83744	514.90916	2053.33249
4476	169	4482	175	33.33520	292.52428	-51.29365	-51.48305	1732.18018	2144.07568
4476	169	4553	218	34.63856	293.55638	-47.98283	-48.35899	1115.11148	1714.92035
4476	169	2094	382	27.67280	288.38274	-58.62898	-57.25110	4378.14001	2002.44388
4476	169	1710	73	30.58033	290.44606	-58.16207	-57.57306	3025.93799	1970.30901
4334	82	4610	255	35.07880	289.78633	-51.44165	-51.51245	1882.11766	3329.28116
4334	82	4624	278	38.29404	292.52493	-46.23445	-46.01506	340.31153	3200.98703
4334	82	4482	175	35.89852	290.46118	-49.84351	-49.84628	1491.41762	3357.28058
4334	82	4553	218	37.11724	291.49323	-48.38054	-48.47816	907.62082	2895.14792
4334	82	1710	73	33.31663	288.38353	-56.32588	-56.58433	2717.12689	3249.20496
4604	249	4610	255	33.33507	291.17394	-52.53151	-53.07022	1783.27779	2505.90063
4604	249	4624	278	36.70145	293.91276	-45.11979	-45.46606	182.41389	2436.21045
4604	249	4482	175	34.19322	291.84882	-50.79486	-51.44217	1377.85480	2548.61484
4604	249	4553	218	35.46865	292.88094	-47.71143	-48.47261	771.75292	2108.57404
4604	249	2094	382	28.64370	287.70745	-55.68188	-55.99393	3979.45212	2450.49774
4604	249	1710	73	31.49521	289.77079	-56.72089	-57.42927	2649.26337	2396.45407
4604	249	2151	422	26.14844	285.99549	-50.69884	-51.54139	5133.90637	2391.24704
4662	160	4553	218	37.89196	290.81810	-47.82329	-48.18358	535.48232	3267.14432
4391	117	4482	175	37.89222	288.75386	-48.02431	-48.74884	532.98451	4311.45142
1974	294	4610	255	33.37986	291.13981	-52.75601	-53.10049	1688.78401	2526.51672
1974	294	4624	278	36.74193	293.87828	-45.17331	-45.43630	91.68554	2455.56882
1974	294	4482	175	34.23519	291.81462	-50.86586	-51.42990	1284.28571	2568.91663
1974	294	4553	218	35.31037	292.84657	-48.20100	-48.53621	679.60391	2128.40247
1974	294	2094	382	28.69168	287.67375	-55.64155	-56.06182	3880.30493	2472.67120
1974	294	1710	73	31.54072	289.73684	-56.99466	-57.48225	2552.85614	2417.68823
1974	294	2151	422	26.19841	285.96199	-51.02344	-51.39341	5032.57422	2414.17776
1976	462	4610	255	34.23416	290.46656	-52.99675	-53.02664	1202.31419	2929.42444
1976	462	4482	175	35.07230	291.14130	-51.52079	-51.52854	805.12060	2964.67441
1976	462	4553	218	36.31389	292.17323	-48.26258	-49.19711	211.50906	2513.41693
1976	462	2094	382	29.64004	287.00087	-55.10346	-55.01818	3356.01572	2911.67218
1976	462	1710	73	32.43319	289.06383	-56.91784	-56.98485	2051.03781	2834.84293
1976	462	2151	422	27.19248	285.28925	-50.34713	-50.47452	4489.88635	2871.02502
2102	387	4610	255	34.25205	290.45231	-52.33857	-52.98447	1478.91104	2937.87918
2102	387	4482	175	35.08976	291.12711	-50.66233	-51.48080	1081.68381	2972.95511
2102	387	4553	218	36.33569	292.15907	-48.16755	-49.26047	488.02897	2521.43231
2102	387	2094	382	29.66026	286.98638	-55.05340	-55.05228	3632.77325	2921.04388
2102	387	1710	73	32.45202	289.04948	-56.81059	-56.96498	2327.69366	2843.66019
2102	387	2151	422	27.21384	285.27465	-51.23919	-50.52425	4766.73928	2880.85709
1178	104	4610	255	35.05774	289.80349	-51.47779	-51.57277	1606.56949	3319.29059

TABLE 8

1178	104	4624	278	38,27536	292,54158	-46,46430	-46,03265	67,42700	3191,98083
1178	104	4482	175	35,87807	290,47823	-50,02304	-49,83742	1216,52719	3347,54004
1178	104	4553	218	37,09769	291,51006	-48,14527	-48,50958	633,73615	2885,77856
1178	104	2094	392	30,55628	286,33811	-54,91659	-54,98199	3723,01672	3337,09067
1178	104	1710	73	33,29428	288,40095	-55,91979	-56,59882	2440,21732	3238,70004
1178	104	2151	422	28,15411	284,62661	-51,34346	-51,75623	4838,60590	3314,17050
3552	879	4610	255	33,39451	291,12839	-46,94230	-53,11638	1844,67471	2533,40982
3552	879	4624	278	36,75532	293,86686	-41,20212	-45,43241	246,14857	2461,97546
3552	879	4482	175	34,25052	291,80320	-45,19866	-51,43007	1439,82391	2575,68604
3552	879	4553	218	35,52424	292,83518	-43,01505	-48,55303	834,60037	2134,99152
3552	879	2094	392	28,70793	287,66233	-46,75507	-56,04250	4038,01172	2480,18259
3552	879	1710	73	31,55501	289,72542	-49,95378	-57,49687	2709,48355	2424,82361
3552	879	2151	422	26,21544	285,95057	-40,58103	-51,34337	5191,16931	2421,99570
1718	81	4610	255	31,57794	292,51498	-52,79746	-52,65171	1672,58382	1681,29201
1718	81	4624	278	35,09123	295,25341	-44,53096	-45,06153	16,48501	1669,41060
1718	81	4482	175	32,47180	293,18975	-50,64760	-50,70387	1253,44106	1738,45343
1718	81	4553	218	33,80306	294,22169	-47,88057	-48,04806	626,49030	1320,18997
1718	81	2094	392	26,69729	289,04887	-58,22546	-58,05201	3939,24167	1553,52240
1718	81	1710	73	29,66031	291,11182	-57,16647	-57,30741	2567,31482	1543,11702
1718	81	2151	422	24,11172	287,33712	-52,86048	-52,86401	5127,53009	1458,96642
1988	303	4610	255	29,71754	293,87719	-52,42044	-52,65150	1959,16600	814,55627
1988	303	4624	278	33,38137	296,61583	-44,07055	-44,13325	243,44985	861,44814
1988	303	4482	175	30,64854	294,55204	-50,80455	-51,70658	1525,30772	886,32440
1988	303	4553	218	32,03658	295,58401	-44,49924	-44,72337	875,87438	490,18060
1988	303	2094	392	24,64896	290,41068	-58,42932	-58,69779	4300,31201	614,65333
1988	303	1710	73	27,72268	292,47371	-55,49784	-55,92331	2884,51242	647,50870
1988	303	2151	422	21,97517	288,49878	-53,67839	-54,06509	5523,58356	485,65553

TABLE 8 (Cont.)

CHARLY-DYNAMIC CORE ALLOCATOR-  
 1089 WORDS OF CORE HAVE BEEN  
 DISTRIBUTED AMONG THE FOLLOWING ARRAYS

SNREV	9
NSREV	12
SUM1	72
SUM2	16
DELTA	16
BBIAS	8
KNSTR	2
ARRAY	956

STARTING ADDRESSES OF ARRAYS

SNREV	126700000000
NSREV	126710000000
SUM1	126724000000
SUM2	127034000000
DELTA	127054000000
BBIAS	127074000000
KNSTR	127104000000
ARRAY	127106000000

51

ORIGINAL PAGE IS  
 OF POOR QUALITY

TABLE 9

\*\*\*BIASES\*\*\*  
 NORTH-TO-SOUTH REVS  
 REV NO    SEG NO    COEFFICIENTS  
 4476    169    0.2166438E-14  
 4334    82    0.2608515E 00  
 4604    249    0.7391857E 00  
 4462    160    0.4181491E 00  
 4391    117    0.6481592E 00  
 1974    294    0.5489130E 00  
 1576    462    0.2523978E 00  
 2102    387    0.4047830E 00  
 1178    104    0.2481538E 00  
 3552    879    0.7254924E 01  
 1718    91    0.2282054E 00  
 1988    303    0.5026312E 00

SOUTH-TO-NORTH REVS  
 REV NO    SEG NO    COEFFICIENTS  
 4610    255    0.2482993E 00  
 4624    278    0.5447675E 00  
 4482    175    0.1236266E 00  
 4553    218    0.5784947E-01  
 2074    382    0.1714784E 00  
 1730    73    0.5747062E-01  
 2151    422    0.2476388E 00

TABLE 10

REVOLUTIONS		CROSSING PTS.		BIASES		A PRIORI SEA SURFACE HEIGHTS		ADJUSTED SEA SURFACE HEIGHTS		AVERAGE	RESIDUALS
N/S	S/N	LATITUDE	LONGITUDE	N/S	N/S	S/N	N/S	S/N	N/S	(ADJUSTED)	N/S
		(DEGREES)	(DEGREES)	(METERS)	(METERS)	(METERS)	(METERS)	(METERS)	(METERS)	(METERS)	(METERS)
4470	4610	32.459675	291.849354	-0.0000	0.2483	-53.4137	-53.2166	-53.4137	-53.4849	-53.4493	0.0356
4476	4624	33.399035	294.588226	-0.0000	0.5848	-44.4345	-44.8374	-44.4845	-45.4222	-44.9533	0.4689
4476	4482	33.335204	292.524251	-0.0000	0.1236	-51.2937	-51.4830	-51.2937	-51.6067	-51.4502	0.1565
4476	4553	34.638564	293.596377	-0.0000	0.0578	-47.9328	-48.3590	-47.9828	-48.4168	-48.1998	0.2170
4476	2094	27.672798	288.382736	-0.0000	0.1715	-58.6290	-57.2311	-58.6290	-57.4026	-58.0158	-0.6132
4476	1710	30.580333	290.446050	-0.0000	0.0595	-58.1621	-57.5731	-58.1621	-57.6325	-57.8973	-0.2648
4334	4610	35.378804	289.786335	0.2609	0.2883	-51.4417	-51.5124	-51.7025	-51.7807	-51.7416	0.0391
4334	4624	38.294036	292.524925	0.2609	0.5848	-46.2345	-46.0151	-46.4953	-46.5998	-46.5476	0.0523
4334	4482	35.898524	290.461178	0.2609	0.1236	-49.8435	-49.8463	-50.1044	-49.9699	-50.0371	-0.0672
4334	4553	37.117242	291.493225	0.2609	0.0578	-48.3305	-48.4782	-48.6414	-48.5360	-48.5887	-0.0527
4334	1710	33.316635	288.383526	0.2609	0.0595	-56.3259	-56.5843	-56.5867	-56.6438	-56.6153	0.0285
4604	4610	33.336068	291.273943	0.7392	0.2483	-52.5315	-53.0702	-53.2707	-53.3385	-53.3046	0.0339
4604	4624	36.701446	293.912762	0.7392	0.5848	-45.1198	-45.4661	-45.8590	-46.0508	-45.9549	0.0959
4604	4482	34.193219	291.848816	0.7392	0.1236	-50.7949	-51.4422	-51.5341	-51.5658	-51.5499	0.0159
4604	4553	35.468647	292.880936	0.7392	0.0578	-47.7114	-48.4726	-48.4506	-48.5305	-48.4905	0.0399
4604	2094	28.643783	287.707451	0.7392	0.1715	-55.6819	-55.9939	-56.4211	-56.1654	-56.2932	-0.1278
4604	1710	31.495209	289.770786	0.7392	0.0595	-56.7209	-57.4293	-57.4601	-57.4887	-57.4744	0.0143
4604	2151	26.148443	285.995491	0.7392	0.2476	-50.6988	-51.5414	-51.4380	-51.2937	-51.3659	-0.0721
4462	4553	37.891960	290.818096	0.4181	0.0578	-47.8233	-48.1836	-48.2414	-48.2414	-48.2414	0.
4394	4482	37.892222	288.753857	0.8482	0.1236	-48.0243	-48.7488	-48.8725	-48.8725	-48.8725	0.

ORIGINAL PAGE IS  
OF POOR QUALITY

TABLE 11



1974	4610	33.379863	291.139809	0.5389	0.2583	-52.7560	-53.1005	-53.2949	-53.3688	-53.3319	0.0369
1974	4624	36.741929	293.878277	0.5389	0.5848	-45.1733	-45.4363	-45.7122	-46.0211	-45.8666	0.1544
1974	4482	34.236194	291.814617	0.5389	0.1236	-50.8659	-51.4299	-51.4048	-51.5535	-51.4792	0.0744
1974	4553	35.510372	292.846565	0.5389	0.0578	-48.2010	-48.5362	-48.7399	-48.5941	-48.6670	-0.0729
1974	2094	28.691679	287.673752	0.5389	0.1715	-55.4416	-56.0318	-56.1805	-56.2033	-56.1919	0.0114
1974	1710	31.540717	289.736835	0.5389	0.0595	-56.9947	-57.4823	-57.5336	-57.5417	-57.5376	0.0041
1974	2151	26.198408	285.961994	0.5389	0.2876	-51.0234	-51.3934	-51.5624	-51.1458	-51.3541	-0.2083
1976	4610	34.234157	290.466564	0.2524	0.2583	-52.9967	-53.0266	-53.2491	-53.2949	-53.2720	0.0229
1976	4482	35.072296	291.141300	0.2524	0.1236	-51.5208	-51.5285	-51.7732	-51.6522	-51.7127	-0.0605
1976	4553	36.318888	292.173225	0.2524	0.0578	-48.2626	-49.1971	-48.5150	-49.2550	-48.8850	0.3700
1976	2094	29.640040	287.600666	0.2524	0.1715	-55.1035	-55.0182	-55.3559	-55.1897	-55.2728	-0.0831
1976	1710	32.433189	289.663931	0.2524	0.0595	-56.9178	-56.9848	-57.1702	-57.0443	-57.1073	-0.0630
1976	2151	27.192479	285.289246	0.2524	0.2876	-50.3471	-50.4745	-50.5995	-50.2269	-50.4132	-0.1863
2102	4610	34.252049	290.452312	0.4048	0.2583	-52.3386	-52.9845	-52.7434	-53.2528	-52.9981	0.2547
2102	4482	35.089757	291.127106	0.4048	0.1236	-50.6623	-51.4808	-51.0671	-51.6044	-51.3358	0.2687
2102	4553	36.335685	292.159065	0.4048	0.0578	-48.1676	-49.2605	-48.5723	-49.3183	-48.9453	0.3730
2102	2094	29.660255	286.986382	0.4048	0.1715	-55.0534	-55.0523	-55.4582	-55.2238	-55.3410	-0.1172
2102	1710	32.452020	289.649180	0.4048	0.0595	-56.8106	-56.9650	-57.2154	-57.0245	-57.1199	-0.0955
2102	2151	27.213644	285.274654	0.4048	0.2876	-51.2392	-50.5242	-51.6440	-50.2766	-50.9603	-0.6837
1378	4610	35.057742	289.803490	0.2882	0.2583	-51.4778	-51.5728	-51.7659	-51.8411	-51.8035	0.0376
1378	4624	38.275364	292.541580	0.2882	0.5848	-46.4643	-46.0327	-46.7525	-46.6174	-46.6849	-0.0675
1378	4482	35.878066	290.478233	0.2882	0.1236	-50.0230	-49.8374	-50.3112	-49.9610	-50.1361	-0.1751

TABLE 11 (Cont.)

1178	4553	37.097687	291.510763	0.2882	0.0578	-48.1453	-48.5096	-48.4334	-48.5674	-48.5004	0.0670
1178	2094	30.556280	286.838108	0.2882	0.1715	-54.9166	-54.9820	-55.2047	-55.1535	-55.1791	-0.0256
1178	1710	33.294276	288.400948	0.2882	0.0595	-55.9198	-56.5988	-56.2079	-56.6583	-56.4331	0.2252
1178	2151	28.154114	284.526306	0.2882	0.2876	-51.3435	-51.7562	-51.6316	-51.5086	-51.5701	-0.0615
3552	4610	33.394506	291.228191	7.2549	0.2883	-46.9423	-53.1164	-54.1972	-53.3847	-53.7909	-0.4063
3552	4624	36.755324	293.866436	7.2549	0.5848	-41.2021	-45.4324	-48.4570	-46.0172	-47.2371	-1.2199
3552	4482	34.250523	291.803204	7.2549	0.1236	-45.1987	-51.4301	-52.4536	-51.5537	-52.0036	-0.4499
3552	4553	35.524237	292.835178	7.2549	0.0578	-43.0151	-48.5830	-50.2700	-48.6109	-49.4404	-0.8295
3552	2094	28.707930	287.562331	7.2549	0.1715	-46.7551	-56.0425	-54.0100	-56.2140	-55.1120	1.1020
3552	1710	31.556008	289.725418	7.2549	0.0595	-49.9538	-57.4969	-57.2087	-57.5563	-57.3825	0.1738
3552	2151	26.215442	285.950365	7.2549	0.2876	-40.5810	-51.3434	-47.8360	-51.0957	-49.4658	1.6299
1718	4610	31.577943	292.514776	0.2282	0.2883	-52.7975	-52.6517	-53.0257	-52.9200	-52.9728	-0.0528
1718	4624	35.091232	295.253107	0.2282	0.5848	-44.5310	-45.0615	-44.7592	-45.6463	-45.2027	0.4436
1718	4482	32.471801	293.189754	0.2282	0.1236	-50.5476	-50.7039	-50.8758	-50.8275	-50.8517	-0.0242
1718	4553	33.803059	294.221587	0.2282	0.0578	-47.8806	-48.0481	-48.1088	-48.1059	-48.1073	-0.0014
1718	2094	26.697291	289.848370	0.2282	0.1715	-58.2255	-58.0520	-58.4537	-58.2235	-58.3386	-0.1151
1718	1710	29.660306	291.111324	0.2282	0.0595	-57.1665	-57.3074	-57.3947	-57.3669	-57.3808	-0.0139
1718	2151	24.111718	287.837124	0.2282	0.2876	-52.3605	-52.8640	-53.0887	-52.6164	-52.8525	-0.2362
1988	4610	29.717535	293.877193	0.5026	0.2883	-52.4204	-52.6515	-52.9231	-52.9198	-52.9214	-0.0016
1988	4624	33.381367	296.615329	0.5026	0.5848	-44.0706	-44.1333	-44.5732	-44.7180	-44.6456	0.0724
1988	4482	30.648543	294.552044	0.5026	0.1236	-50.8046	-51.7066	-51.3072	-51.8302	-51.5687	0.2615
1988	4553	32.036525	295.584011	0.5026	0.0578	-44.4992	-44.7234	-45.0019	-44.7812	-44.8915	-0.1103

ORIGINAL PAGE IS  
OF POOR QUALITY

TABLE 11 (Cont.)

1988	2094	24.648965	290.410675	0,5026	0,1715	-58.4293	-58,6978	-58,9320	-58,8693	-58,9096	-0.0313
1988	1710	27.722684	292.473713	0,5026	0,0595	-55,4978	-55,9233	-56,0005	-55,9828	-55,9916	-0.0088
1988	2151	21.975166	288,898776	0,5026	0,2876	-53,6784	-54,0651	-54,1810	-53,8175	-53,9992	-0.1818
MEAN OF RESIDUALS		-0,00000									
STANDARD DEVIATION		0,57305									

TABLE 11 (Cont.)

REVOLUTIONS		CROSSING PTS.		BIASES		A PRIORI SEA SURFACE HEIGHTS		ADJUSTED SEA SURFACE HEIGHTS		AVERAGE (ADJUSTED)	RESIDUALS
S/N	N/S	LATITUDE (DEGREES)	LONGITUDE (DEGREES)	S/N (METERS)	S/N (METERS)	N/S (METERS)	S/N (METERS)	N/S (METERS)	S/N (METERS)	(METERS)	S/N (METERS)
4610	4476	32.459675	291.849354	0.2683	0.0000	-53.2166	-53.4137	-53.4849	-53.4137	-53.4493	-0.0356
4610	4334	35.078804	289.786355	0.2683	0.2809	-51.5124	-51.4417	-51.7807	-51.7025	-51.7416	-0.0391
4610	4604	33.336068	291.173943	0.2683	0.7392	-53.0702	-52.5315	-53.3385	-53.2707	-53.3046	-0.0339
4610	1974	33.379863	291.139309	0.2683	0.5389	-53.1005	-52.7560	-53.3688	-53.2949	-53.3319	-0.0369
4610	1576	34.234157	290.866564	0.2683	0.2524	-53.0266	-52.9967	-53.2949	-53.2491	-53.2720	-0.0229
4610	2102	34.252049	290.852312	0.2683	0.4848	-52.9845	-52.3386	-53.2528	-52.7434	-52.9981	-0.2547
4610	1178	35.057742	289.883490	0.2683	0.2882	-51.5728	-51.4778	-51.8411	-51.7659	-51.8035	-0.0376
4610	3552	33.394506	291.828391	0.2683	7.2549	-53.1164	-46.9423	-53.3847	-54.1972	-53.7909	0.4063
4610	1718	31.577943	292.514976	0.2683	0.2282	-52.6517	-52.7975	-52.9200	-53.0257	-52.9728	0.0528
4610	1988	29.717535	293.877193	0.2683	0.5826	-52.6515	-52.4204	-52.9198	-52.9231	-52.9214	0.0016
4624	4476	35.899035	294.586226	0.5848	0.0000	-44.8374	-44.4845	-45.4222	-44.4845	-44.9533	-0.4689
4624	4334	36.294036	292.524925	0.5848	0.2809	-46.0151	-46.2345	-46.5998	-46.4953	-46.5476	-0.0523
4624	4604	36.701446	293.912762	0.5848	0.7392	-45.4661	-45.1198	-46.0508	-45.8590	-45.9549	-0.0959
4624	1974	36.741929	293.878277	0.5848	0.5389	-45.4363	-45.1733	-46.0211	-45.7122	-45.8666	-0.1544
4624	1178	36.275364	292.541580	0.5848	0.2282	-46.0327	-46.4643	-46.6174	-46.7525	-46.6849	0.0675
4624	3552	36.755324	293.866356	0.5848	7.2549	-45.4324	-41.2021	-46.0172	-48.4570	-47.2371	1.2199
4624	1718	35.091232	295.253407	0.5848	0.2282	-45.0615	-44.5310	-45.6463	-44.7592	-45.2027	-0.4436
4624	1988	33.381367	296.615829	0.5848	0.5826	-44.1333	-44.0706	-44.7180	-44.5732	-44.6456	-0.0724
4682	4476	33.335204	292.524281	0.1236	0.0000	-51.4830	-51.2937	-51.6067	-51.2937	-51.4502	-0.1565
4682	4334	35.898524	290.861178	0.1236	0.2809	-49.8463	-49.8435	-49.9699	-50.1044	-50.0371	0.0672

TABLE 12

ORIGINAL PAGE IS  
OF POOR QUALITY

4482	4604	34.193219	291.848816	0.1236	0.7392	-51.4422	-50.7949	-51.5658	-51.5341	-51.5499	-0.0159
4482	4391	37.892222	288.753357	0.1236	0.8882	-48.7488	-48.0243	-48.8725	-48.8725	-48.8725	0.
4482	1974	34.236194	291.814617	0.1236	0.5389	-51.4299	-50.8659	-51.5535	-51.4048	-51.4792	-0.0744
4482	1576	35.072296	291.141300	0.1236	0.2524	-51.5285	-51.5208	-51.6522	-51.7732	-51.7127	0.0605
4482	2102	35.089757	291.127106	0.1236	0.4048	-51.4808	-50.6623	-51.6044	-51.0671	-51.3358	-0.2687
4482	1178	35.878066	290.478233	0.1236	0.2882	-49.8374	-50.0230	-49.9610	-50.3112	-50.1361	0.1751
4482	3552	34.250523	291.807204	0.1236	7.2549	-51.4301	-45.1987	-51.5537	-52.4536	-52.0036	0.4499
4482	1718	32.471801	293.189754	0.1236	0.2282	-50.7039	-50.6476	-50.8275	-50.8758	-50.8517	0.0242
4482	1988	30.648543	294.552044	0.1236	0.5026	-51.7066	-50.8046	-51.8302	-51.3072	-51.5687	-0.2615
4553	4476	34.638564	293.556377	0.0578	*0.0000	-48.3590	-47.9828	-48.4168	-47.9828	-48.1998	-0.2170
4553	4334	37.117242	291.497225	0.0578	0.2609	-48.4782	-48.3805	-48.5360	-48.6414	-48.5887	0.0527
4553	4604	35.468647	292.881936	0.0578	0.7392	-48.4726	-47.7114	-48.5305	-48.4506	-48.4905	-0.0399
4553	4462	37.891960	290.818096	0.0578	0.4181	-48.1836	-47.8233	-48.2414	-48.2414	-48.2414	0.
4553	1974	35.510372	292.840565	0.0578	0.5389	-48.5362	-48.2010	-48.5941	-48.7399	-48.6670	0.0729
4553	1576	34.318888	292.173225	0.0578	0.2524	-49.1971	-48.2626	-49.2550	-48.5150	-48.8850	-0.3700
4553	2102	36.335685	292.159065	0.0578	0.4048	-49.2605	-48.1676	-49.3183	-48.5723	-48.9453	-0.3730
4553	1178	37.097687	291.510063	0.0578	0.2882	-48.5096	-48.1453	-48.5674	-48.4334	-48.5004	-0.0670
4553	3552	35.524237	292.835178	0.0578	7.2549	-48.5530	-43.0151	-48.6109	-50.2700	-49.4404	0.8295
4553	1718	33.803059	294.221687	0.0578	0.2282	-48.0481	-47.8806	-48.1059	-48.1088	-48.1073	0.0014
4553	1988	32.036575	295.984011	0.0578	0.5026	-44.7234	-44.4992	-44.7812	-45.0019	-44.8915	0.1103
2094	4476	27.672798	288.882736	0.1715	*0.0000	-57.2311	-58.6290	-57.4026	-58.6290	-58.0158	0.6132
2094	4604	28.643703	287.707451	0.1715	0.7392	-55.9939	-55.6819	-56.1654	-56.4211	-56.2932	0.1278

TABLE 12 (Cont.)

2094	1974	28,691679	287,675752	0.1715	0.5389	-56.0318	-55.6416	-56.2033	-56.1805	-56.1919	-0.0114
2094	1576	29.640040	287,500866	0.1715	0.2524	-55.0182	-55.1035	-55.1897	-55.3559	-55.2728	0.0831
2094	2102	29.660255	286,986382	0.1715	0.4048	-55.0523	-55.0534	-55.2238	-55.4582	-55.3410	0.1172
2094	1178	30.556280	286,339108	0.1715	0.2882	-54.9820	-54.9166	-55.1535	-55.2047	-55.1791	0.0256
2094	3552	29.707930	287,862331	0.1715	7.2549	-56.0425	-46.7551	-56.2140	-54.0100	-55.1120	-1.1020
2094	1718	26.697291	289,049870	0.1715	0.2282	-58.0520	-58.2255	-58.2235	-58.4537	-58.3386	0.1151
2094	1988	24.648965	290,410675	0.1715	0.5826	-58.6978	-58.4293	-58.8693	-58.9320	-58.9006	0.0313
1718	4476	30.580333	290,440660	0.0595	0.0000	-57.5731	-58.1621	-57.6325	-58.1621	-57.8973	0.2648
1718	4334	33.316635	288,383526	0.0595	0.2809	-56.5843	-56.3259	-56.6438	-56.5867	-56.6153	-0.0285
1718	4604	31.495209	289,773786	0.0595	0.7392	-57.4293	-56.7209	-57.4887	-57.4601	-57.4744	-0.0143
1718	1974	31.540717	289,735835	0.0595	0.5389	-57.4823	-56.9947	-57.5417	-57.5336	-57.5376	-0.0041
1718	1576	32.433189	289,463831	0.0595	0.2524	-56.9848	-56.9178	-57.0443	-57.1702	-57.1073	0.0630
1718	2102	32.452020	289,443480	0.0595	0.4048	-56.9650	-56.8106	-57.0245	-57.2154	-57.1199	0.0955
1718	1178	33.294276	288,403948	0.0595	0.2882	-56.5988	-55.9198	-56.6583	-56.2079	-56.4331	-0.2252
1718	3552	31.556008	289,725418	0.0595	7.2549	-57.4969	-49.9538	-57.5563	-57.2087	-57.3825	-0.1738
1718	1718	23.660306	291,111824	0.0595	0.2282	-57.3074	-57.1665	-57.3669	-57.3947	-57.3808	0.0139
1718	1988	27.722684	292,473713	0.0595	0.5026	-55.9233	-55.4978	-55.9828	-56.0005	-55.9916	0.0088
2151	4604	26.148443	285,995491	-0.2476	0.7392	-51.5414	-50.6988	-51.2937	-51.4380	-51.3659	0.0721
2151	1974	26.198408	285,961994	-0.2476	0.5389	-51.3934	-51.0234	-51.1458	-51.5624	-51.3541	0.2083
2151	1576	27.192479	285,289246	-0.2476	0.2524	-50.4745	-50.3471	-50.2269	-50.5995	-50.4132	0.1863
2151	2102	27.213844	285,274654	-0.2476	0.4048	-50.5242	-51.2592	-50.2766	-51.6440	-50.9603	0.6837
2151	1178	28.154114	284,625606	-0.2476	0.2882	-51.7562	-51.3435	-51.5086	-51.6316	-51.5701	0.0615

ORIGINAL PAGE IS  
OF POOR QUALITY

TABLE 12 (Cont.)

2151	3552	26.215442	285.950565	-0.2476	7.2249	-51.3434	-40.5810	-51.0957	-47.8360	-49.4658	-1.6299
2151	1718	24.111718	287.837124	-0.2476	0.2282	-52.8640	-52.8605	-52.6164	-53.0887	-52.8525	0.2362
2151	1988	21.975166	288.899776	-0.2476	0.5026	-54.0651	-53.6784	-53.8175	-54.1810	-53.9992	0.1818

TABLE 12 (Cont.)

SEAHT

LEAST SQUARES DETERMINATION OF SMOOTHED SEA SURFACE HEIGHTS  
CALCULATED AT INTERSECTING POINTS OF CROSSING REVOLUTIONS

CALIBRATION AREA  
LATITUDE 55.00 TO 67.00  
LONGITUDE 300.00 TO 330.00

NO. OF PARAMETERS \* 1

NO. OF SOUTH-TO-NORTH REVS \* 9

NO. OF NORTH-TO-SOUTH REVS \* 8

TABLE 13



NORTH-TO-SOUTH REVOLUTIONS	
REV NO	SES NO
640	563
2658	360
2929	479
4236	15
4577	232
4562	222
626	556
4548	213

SOUTH-TO-NORTH REVOLUTIONS	
REV NO	SES NO
640	563
2638	360
2673	376
2829	479
4236	15
626	556
663	591
641	564
1167	101

TABLE 14

\*\*\*\*\*CONSTRAINED REVS\*\*\*\*\*

REV NO	SEG NO	TYPE OF CONSTRAINT		
		HEIGHT	SLOPE	CURVATURE
4236	15	*		
4548	213	*		

ORIGINAL PAGE IS  
OF POOR QUALITY

ARC CROSSING DATA INPUT FOR THIS RUN

REVOLUTION NO				CROSSING POINTS		SMOOTHED SEA SURFACE HEIGHT		TIME FROM EPOCH	
NORTH-SOUTH	SOUTH-NORTH	NORTH-SOUTH	SOUTH-NORTH	LATITUDE	LONGITUDE	NORTH-SOUTH	SOUTH-NORTH	NORTH-SOUTH	SOUTH-NORTH
(REV/SEC)	(REV/SEC)	(REV/SEC)	(REV/SEC)	(DEGREES)	(DEGREES)	(METERS)	(METERS)	(MINUTES)	(MINUTES)
640	563	640	563	65.13433	306.99883	22.42969	22.42969	-1.74089	-1.74089
2658	360	2658	360	65.12445	325.57243	60.85156	60.85156	8.37898	8.37898
2658	360	2829	479	65.04635	320.82355	50.11682	44.53372	8.93182	14.04771
4236	15	2829	479	65.04442	320.91197	43.00198	44.65421	5.74540	14.03740
4236	15	4236	15	65.12493	325.38430	51.92188	51.92188	5.22387	5.22387
4577	232	640	563	64.72019	319.71224	44.83345	33.16425	5.63083	-3.22911
4577	232	2829	479	64.64519	323.33159	52.49392	51.06031	5.20089	13.75370
4562	222	640	563	63.66492	329.57867	54.66899	56.53514	4.83760	-4.44844
4562	222	2673	376	63.49440	328.43145	52.87172	52.48216	4.98651	5.29311
4562	222	641	564	61.13342	316.89210	64.98653	41.40091	6.60434	9.03104
4562	222	1167	101	61.11054	316.83937	55.67219	64.53549	6.61237	8.64328
626	556	626	556	65.12077	300.44065	11.14063	11.14063	16.57750	16.57750

TABLE 16

# ARC CROSSING DATA USED FOR ADJUSTMENTS

REVOLUTION NO				CROSSING POINTS		SMOOTHED SEA SURFACE HEIGHT		TIME FROM EPOCH	
NORTH-SOUTH	SOUTH-NORTH	NORTH-SOUTH	SOUTH-NORTH	LATITUDE	LONGITUDE	NORTH-SOUTH	SOUTH-NORTH	NORTH-SOUTH	SOUTH-NORTH
(REV/SEC)	(REV/SEC)	(REV/SEC)	(REV/SEC)	(DEGREES)	(DEGREES)	(METERS)	(METERS)	(MINUTES)	(MINUTES)
640	563	640	563	65.13433	306.99883	22.42969	22.42969	-1.74089	-1.74089
2658	360	2658	360	65.12045	325.57243	60.85156	60.85156	8.37898	8.37898
2658	360	2629	479	65.04635	320.82355	50.11682	44.53872	8.93132	14.04771
4236	15	2829	479	65.04342	320.91197	43.00198	44.65421	5.74540	14.03740
4236	15	4236	15	65.12493	325.38430	51.92188	51.92188	5.22387	5.22387
4577	232	640	563	64.72919	319.71224	44.83345	33.16425	5.63083	-3.22911
4577	232	2829	479	64.94519	323.33159	52.49392	51.06031	5.20089	13.75370
4562	222	640	563	63.66482	329.57867	54.66899	56.53514	4.83760	-4.44844
4562	222	2673	376	63.49440	328.43145	52.87172	52.48216	4.98651	5.29311
4562	222	641	564	61.13342	316.89210	64.98653	41.40091	6.60434	9.03104
4562	222	1167	101	61.11954	316.83937	55.67219	64.93549	6.61237	8.64328
626	556	626	556	65.12077	300.44065	11.14063	11.14063	16.57750	16.57750

ORIGINAL PAGE IS  
OF POOR QUALITY

TABLE 17

CHARLY-DYNAMIC CORE ALLOCATOR-

599WORDS OF CORE HAVE BEEN  
DISTRIBUTED AMONG THE FOLLOWING ARRAYS

SNREV	8
NSREV	6
SUM1	90
SUM2	18
DELTA	18
BBIAS	10
KNSTR	2
ARRAY	448

STARTING ADDRESSES OF ARRAYS

SNREV	127426000000
NSREV	127436000000
SLM1	127444000000
SLM2	127576000000
DELTA	127620000000
BBIAS	127642000000
KNSTR	127654000000
ARRAY	127656000000

DIV CHECK AT LOCATION 024507

2  
2

\*\*\*\*\*BIASES\*\*\*\*\*  
NORTH TO SOUTH REVS

REV NO	SEG NO	COEFFICIENTS
640	563	-0.8583354E 01
2658	360	0.7230325E 01
4236	19	-0.9595514E-15
4577	232	0.3085838E 01
4562	222	-0.1044951E 02
626	558	0.

SOUTH TO NORTH REVS

REV NO	SEG NO	COEFFICIENTS
640	563	-0.8583354E 01
2658	360	0.7230326E 01
2673	378	-0.1083907E 02
2829	479	0.1652231E 01
4236	19	0.
626	556	0.
641	564	-0.3403513E 02
1167	101	-0.1586218E 01

REVOLUTIONS		CROSSING PTS.		BIASES		SEA SURFACE HEIGHTS		SEA SURFACE HEIGHTS		AVERAGE	RESIDUALS
N/S	S/N	LATITUDE (DEGREES)	LONGITUDE (DEGREES)	N/S (METERS)	S/N (METERS)	N/S (METERS)	S/N (METERS)	N/S (METERS)	S/N (METERS)	{ADJUSTED} (METERS)	N/S (METERS)
640	640	65:134333	306:998833	-8.5834	-8.5834	22.4297	22.4297	31.0130	31.0130	31.0130	0.
2658	2658	65:129446	325:572426	7.2303	7.2303	60.8516	60.8516	53.6212	53.6212	53.6212	0.
2658	2829	65:046348	320:823555	7.2303	1.6522	50.1168	44.9387	42.8865	42.8865	42.8865	0.
4236	2829	65:043416	320:911968	-0.0000	1.6522	43.0020	44.6542	43.0020	43.0020	43.0020	0.
4236	4236	65:124931	325:384300	-0.0009	0.	51.9219	51.9219	51.9219	51.9219	51.9219	0.
4577	640	64:729195	319:712238	3.0858	-8.5834	44.6334	33.1643	41.7476	41.7476	41.7476	0.
4577	2829	64:945189	323:331593	3.0858	1.6522	52.4939	51.0603	49.4081	49.4081	49.4081	0.
4562	640	63:664815	329:578667	-10.4495	-8.5834	54.6690	56.9351	65.1185	65.1185	65.1185	0.
4562	2673	63:494325	328:431454	-10.4495	-10.8391	52.8717	52.4822	63.3212	63.3212	63.3212	0.
4562	641	61:133418	316:892101	-10.4495	-34.0351	64.9865	41.4009	75.4360	75.4360	75.4360	0.
4562	1167	61:119545	316:839371	-10.4495	-1.5862	55.6722	64.9355	66.1217	66.1217	66.1217	0.
626	626	65:120769	300:440651	0.	0.	11.1406	11.1406	11.1406	11.1406	11.1406	0.
MEAN OF RESIDUALS		0.									
STANDARD DEVIATION		0.									

TABLE 20

REVOLUTIONS		CROSSING PTS.		BIASES		A PRIORI SEA SURFACE HEIGHTS		ADJUSTED SEA SURFACE HEIGHTS		AVERAGE	RESIDUALS
S/A	N/S	LATITUDE (DEGREES)	LONGITUDE (DEGREES)	S/N (METERS)	N/S (METERS)	S/N (METERS)	N/S (METERS)	S/N (METERS)	N/S (METERS)	{ADJUSTED} (METERS)	S/N (METERS)
640	640	65.134333	306.998833	-8.5834	-8.5834	22.4297	22.4297	31.0130	31.0130	31.0130	0.
640	4577	64.729195	319.712238	-8.5834	3.0858	33.1643	44.8334	41.7476	41.7476	41.7476	0.
640	4562	63.664813	329.578667	-8.5834	-10.4495	56.5351	54.8690	65.1185	65.1185	65.1185	0.
2658	2658	65.129448	325.572426	7.2303	7.2303	60.8516	60.8516	53.6212	53.6212	53.6212	0.
2673	4562	63.494395	328.431454	-10.8391	-10.4495	52.4822	52.8717	63.3212	63.3212	63.3212	0.
2829	2658	65.046348	320.923555	1.6522	7.2303	44.5387	50.1168	42.8865	42.8865	42.8865	0.
2829	4236	65.043416	320.911968	1.6522	-0.0000	44.6542	43.0020	43.0020	43.0020	43.0020	0.
2829	4577	64.945139	323.331593	1.6522	3.0858	51.0603	52.4939	49.4081	49.4081	49.4081	0.
4236	4236	65.124931	325.384300	0.	-0.0000	51.9219	51.9219	51.9219	51.9219	51.9219	0.
626	626	65.120769	300.440651	0.	0.	11.1406	11.1406	11.1406	11.1406	11.1406	0.
641	4562	61.133418	316.892101	34.0351	-10.4495	41.4009	64.9865	75.4360	75.4360	75.4360	0.
1167	4562	61.119545	316.839371	-1.5862	-10.4495	64.5335	55.6722	66.1217	66.1217	66.1217	0.

ORIGINAL PAGE IS  
OF POOR QUALITY

TABLE 21



# FORMAT OF SEAHT OUTPUT TAPE

## HEADER RECORD

<u>WORD NO.</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
1	I	Dummy (0)
2	I	Dummy (0)
3	I	No. of Data Records
4	I	Segment No.
5	I	Revolution No.

## DATA RECORD

<u>WORD NO.</u>	<u>FORMAT</u>	<u>DESCRIPTION</u>
1	I	Time (milliseconds)
2	I	Latitude (milliseconds)
3	I	Longitude (milliseconds)
4	I	Sea Surface Height (micrometers)
5	I	Dummy (0)

TABLE 22

### 3.6 LIMITATIONS

Several dimensions have been set in SEAHT to values sufficiently high to accommodate all runs that are expected to be made by the program. The dimensions set produce only the following limitations:

- Number of North-South passes  $\leq 200$
- Number of South-North passes  $\leq 200$
- Number of data records per pass  $\leq 2000$   
( $\approx 33$  minutes at the 1/second data rate)
- Number of Selects/Deletes from one data tape  
 $\leq 50$
- Total number of input data tapes  $\leq 6$ .

Within limits, all the above dimensions could be significantly increased if needed, without increasing the total core used by the program. The arrays used in the parameter estimation portion of the program are all dynamically allocated, and so the number of passes that can be processed depends upon the number of parameters estimated per pass, and the amount of core that is available.

SEAHT will not function properly if:

- Some revolutions do not cross either a constrained revolution, or a revolution which crosses a constrained revolution.

There are no error terminations in SEAHT, and improperly setup jobs may be terminated either via system abort, or by meaningless program output.

SECTION 4.0  
PROGRAM LISTING

A listing of the working version of the program follows.  
The placement of LINK cards is shown.

```

1      CSEAHT-
2      DIMENSION ICORE(8)
3      COMMON/TAPES/INTP, IOUT, GTAP, NSTAPE, SNTAPE, SCRB, SCRC, DATAPE, DOUT
4      COMMON/KONTBL/NOPAR, NQVS, NOSN, IKNSTR, EDIT, MAX
5      EQUIVALENCE(ICORE(1), ICNS), (ICORE(2), ICNS), (ICORE(3), NSUM1),
6      (ICORE(4), NSUM2), (ICORE(5), NDEL), (ICORE(6), NP),
7      (ICORE(7), NKNSTB), (ICORE(8), IMAX)
8      DATA NCORE/8/, IMORE/0/
9      CALL LLINK($HLINK1)
10     CALL SEARCH
11     NP=NOPAR*(NQVS+1)
12     NSUM1=NP*(NP+1)
13     NSUM2=NP*2
14     NDEL=NSUM2
15     ICNS=NOSN
16     ICNS=NQVS
17     NKNSTB=IKNSTR*2
18     IMAX=MAX*4
19     DO 10 I=1, NCORE
20     IMORE=IMORE+ICORE(I)
21     10 IF(MOD(ICORE(I), 2).NE.0) ICORE(I)=ICORE(I)+1
22     KOREB=320
23     WRITE(6,3) IMORE, (ICORE(K), K=1,8)
24     5 FORMAT('1', 4X, 'CHARLY=DYNAMIC CORE ALLOCATOR-', //, I6,
25     'WORDS OF CORE HAVE BEEN', //, 'DISTRIBUTED AMONG THE FOLLOWING',
26     'ARRAYS', //, 10X, 'SNREV', 5X, I6, //, 10X, 'NSREV', 5X, I6, //, 10X, 'SUM1',
27     .6X, I6, //, 10X, 'SUM2', 6X, I6, //, 10X, 'DELTA', 5X, I6, //, 10X, 'BBIAS', 5X, I6,
28     //, 10X, 'KNSTB', 5X, I6, //, 10X, 'ARRAY', 5X, I6)
29     CALL LLINK($HLINK2)
30     CALL LLINK($HLINK3)
31     CALL CHARLY(KOREB, IMORE, NCORE, ICORE, KOREG, $100)
32     GO TO 102
33     100 WRITE(5, 101)
34     101 FORMAT('1', 'CHARLY HAS BEEN UNSUCCESSFUL IN ALLOCATING CORE,')
35     102 CALL LLINK($HLINK4)
36     CALL SOLVE
37     STOP
38     END

```

57345 C1 03-16-77 16.997

```
1      CBDDATA
2      BLOCK DATA
3      INTEGER GTAP,DOUT
4      COMMON/KONTBL/NPARC,NONS,NOSN,IKNSTR,EDIT,MAX
5      COMMON/TAPE8/INTP,IOUT,GTAP,ISCR(5),DOUT
6      DATA INTR/5/,IOUT/6/,ISCR/11,12,13,14,15/,GTAP/18/,DOUT/10/
7      DATA NPARC/8/,NONS/0/,NOSN/0/
8      DATA IKNSTR/0/
9      DATA EDIT/100./
10     DATA MAX/0/
11     END
```

57345 01 03-16-77 16,998

```
1      CNUMBER
2      INTEGER FUNCTION NUMBER(K,IA,ID)
3      DIMENSION IA(ID)
4      NUMBER=0
5      IF(ID.LT.1) RETURN
6      DO 10 I=1,ID
7      IF(K.EQ,IA(I)) GO TO 20
8      10 CONTINUE
9      RETURN
10     20 NUMBER=I
11     RETURN
12     END
```

ORIGINAL PAGE IS  
OF POOR QUALITY

LINK LINK1

[illegible]

NECC-5091



```

1      CSEARCH
2      SUBROUTINE SEARCH
3      EXTERNAL USERR
4      LOGICAL MINUTE
5      LOGICAL NODATA
6      INTEGER DATA(8),SNTAPE,SCRB,REVNQ,CDNAME(11),ICARDID,TAPLIM,UNIQ
7      INTEGER SNREV(200),NSREV(200),CRSNGS(5000,2),NONLEG(200,2),
8          NDELT(2),INTNOS(200,2)
9      INTEGER DATAPE
10     INTEGER SELECT(50,6),DELETE(50,6),KNO(6),KNA(6),ITAPE(6,2)
11     REAL MINLAT,MAXLAT,MINLON,MAXLON
12     DIMENSION WORDS(4),DT1(4),SSHT(2)
13     DIMENSION KNSTR(5000,2)
14     COMMON/KONTBL/NOPAR,NONS,NOSN,IKNSTR,EDIT,MAX
15     COMMON/ALT/BI,ARRAY(4,1000),NJ,ARRY(4,1000)
16     COMMON/TAPES/INTP,OUT,GTAP,NSTAPE,SNTAPE,SCRB,SCRC,DATAPE,DOUT
17     EQUIVALENCE (XCROSS,DATA(3)),(YCROSS,DATA(4)),(GJ,DATA(6)),
18         (TI,DATA(7)),(TJ,DATA(8)),(GI,DATA(5)),SSHT(1))
19     EQUIVALENCE (UNIQ,WORDS(4))
20     DATA NODATA/,FALSE./
21     DATA MINUTE/,TRUE./
22     DATA MINUS/,1./
23     DATA NDELT/2*0/,NCARD/11/,TAPLIM/6/,ITP1/0/,ITAPE/12*0/
24     DATA CDNAME/6HAREA,6HPARAM,6HNODATA,6HCONSTR,6HEDIT,6HDATA,
25     ,6HSELECT,6HDELETE,6HVERTCL,6HZERO,6HMINUTE/
26     DATA KNO/6*0/,KNA/6*0/
27     DATA MINLAT/-90.0/
28     , MAXLAT/90./,
29     , MINLON/000./,
30     , MAXLON/360./
31     DATA ZERO/0.0/
32     DATA IKNSTR/0/
33     DATA EDIT1/1000./
34     INTEGER R,C
35     20 READ(INTR,1002,END=21) CARDID,IARRAY,DT1
36     1002 FORMAT(A6,I4,4E15.5)
37     I=NUMBER(CARDID,CDNAME,NCARD)
38     IF(I.NE.6) GO TO 20
39     ITP1=ITP1+1
40     ITAPE(ITR1,1)=IARRAY
41     K=DT1(1)+0,1
42     ITAPE(ITR1,2)=MAX0(K,1)

```

```

43      GO TO 20
44      21 REWIND INTP
45      6 READ(INTR,1002,END=50) CARDID,IARRAY,DT1
46      I=NUMBER(CARDID,CDNAME,NCARD)
47      GO TO (1,2,3,4,5,6,7,8,9,10,11),I
48      1 MINLAT=DT1(1)
49      MAXLAT=DT1(2)
50      MINLON=DT1(3)
51      MAXLON=DT1(4)
52      GO TO 6
53      2 NOPAR=IARRAY
54      GO TO 6
55      3 NODATA=.TRUE.
56      IF(IARRAY.GT.0) SCR8=IARRAY
57      READ(SCR8) NONS,NOSN
58      GO TO 6
59      4 IKNSTR=IKNSTR+1
60      KNSTR(IKNSTR,1)=DT1(1)*100000.0+DT1(2)*10.0
61      KNSTR(IKNSTR,2)=IARRAY
62      GO TO 6
63      5 EDIT=DT1(1)
64      GO TO 6
65      7 CALL SELDEL(ITP1,ITAPE,IARRAY,DT1,SELECT%KNO)
66      GO TO 6
67      8 CALL SELDEL(ITP1,ITAPE,IARRAY,DT1,DELETE%KNA)
68      GO TO 6
69      9 ISETV=111
70      GO TO 6
71      10 ZERO=DT1(1)
72      WRITE(6,1003) ZERO
73      1003 FORMAT(1X,'A ZERO OPTION USED WITH',R13.5,'LONGITUDE ZERO-SET')
74      GO TO 6
75      11 MINUTE=.FALSE.
76      GO TO 6
77      50 IF(NODATA) RETURN
78      DO 55 I=1,ITP1
79      IUNIT=ITAPE(I,1)
80      NTPASS=ITAPE(I,2)
81      CALL FLGPRC(IUNIT,USERR)
82      DO 90 K=1,NTPASS
83      READ(IUNIT,END=90) WORDS,REVNO
84      REVNO=REVNO#100000+UNIQ*10

```

ORIGINAL PAGE IS  
OF POOR QUALITY

```

85      IF(NUMBER(REVNO,SELECT(1,1),KNO(1)),GT,0) GO TO 60
86      IF(KNO(1),NE,0) GO TO 61
87      IF(NUMBER(REVNO,DELETE(1,1),KNA(1)),EQ,0) GO TO 60
88      61 READ(IUNIT,END=90) WORDS
89      GO TO 61
90      NR=0
91      IPRTL=0
92      M=1
93      65 READ(IUNIT,END=78) WORDS
94      IF(WORDS(2)LT,MINLAT,OR,WORDS(2),GT,MAXLAT) GO TO 65
95      IF(WORDS(3)LT,MINLON,OR,WORDS(3),GT,MAXLON) GO TO 65
96      IF(MINUTE) WORDS(1)=WORDS(1)*1440,
97      ARRAY(1,M)=WORDS(1)
98      ARRAY(2,M)=WORDS(2)
99      ARRAY(3,M)=WORDS(3)
100     ARRAY(4,M)=WORDS(4)
101     IF(M,LE,2) GO TO 74
102     IF(DIFF*(ARRAY(2,M)-ARRAY(2,M-1)).GE,0.0) GO TO 75
103     NR=NR+1
104     BACKSPACE IUNIT
105     IPRTL=1
106     GO TO 79
107     74 IF(M,EQ,2) DIFF=ARRAY(2,2)-ARRAY(2,1)
108     75 NR=NR+1
109     M=M+1
110     IF(M+LE,1000) GO TO 65
111     78 IF(NR,LE,0) GO TO 90
112     79 IF(NR,LE,1.AND,IPRTL,GT,0) GO TO 60
113     IF(NR,GT,MAX) MAX=NR
114     IF(1SETV,EQ,111.AND,(ARRAY(3,2)-ARRAY(3,1)).GT,0.0000001) GO TO 80
115     XS=ARRAY(2,2)-ARRAY(2,1)
116     IF(XS,GT,0.0) GO TO 80
117     NM=NM+1
118     NSREV(NM)=REVNO
119     WRITE(NTAPE) REVNO,NR,ARRAY
120     IF(IPRTL,GT,0) GO TO 60
121     GO TO 90
122     80 NN=NM+1
123     SNREV(NN)=REVNO
124     WRITE(SNTAPE) REVNO,NR,ARRAY
125     IF(IPRTL,GT,0) GO TO 60
126     90 CONTINUE

```

```

127      55 CONTINUE
128      ENDFILE NSTAPE
129      ENDFILE SNTAPE
130      REWIND NSTAPE
131      WRITE(SCRB) NM,NN,NSREV,SNREV
132      DO 200 M=1,NM
133      READ(NSTAPE,END=200) REVNO,NI,ARRAY
134      IF(ZERO,EQ,0.0) GO TO 56
135      DO 57 L=1,NI
136      IF((ARRAY(3,L)-ZERO),GE,0.0) GO TO 58
137      ARRAY(3,L)=ARRAY(3,L)+360.0-ZERO
138      GO TO 57
139      58 ARRAY(3,L)=ARRAY(3,L)-ZERO
140      57 CONTINUE
141      56 REWIND SNTAPE
142      DATA(2)=M
143      EXLNGM=ARRAY(3,1)
144      EXLATM=ARRAY(2,1)
145      ENLNGM=ARRAY(3,NI)
146      ENLATM=ARRAY(2,NI)
147      DO 150 N=1,NN
148      READ(SNTAPE,END=150) REVNO,NJ,ARRY
149      IF(ZERO,EQ,0.0) GO TO 59
150      DO 70 L=1,NJ
151      IF((ARRY(3,L)-ZERO),GE,0.0) GO TO 69
152      ARRY(3,L)=ARRY(3,L)+360.0-ZERO
153      GO TO 70
154      69 ARRY(3,L)=ARRY(3,L)-ZERO
155      70 CONTINUE
156      59 DATA(1)=N
157      ENLATN=ARRY(2,1)
158      ENLNGN=ARRY(3,1)
159      EXLATN=ARRY(2,NJ)
160      EXLNGN=ARRY(3,NJ)
161      D7=(ENLNGM-ENLNGN)*(EXLNGM-EXLNGN)
162      D8=(EXLATN-ENLATM)*(ENLATN-EXLATM)
163      IF(D7.GT,0.0,OR,D8.GT,0.0) GO TO 150
164      CALL CROSS(XCROSS,YCROSS,ENLATM,ENLNGM,EXLATM,EXLNGM,ENLATN,
165      ENLNGN,EXLATN,EXLNGN,INDC)
166      IF(INDC,EQ,1) GO TO 150
167      CALL GHTIM(XCROSS,YCROSS,GI,GJ,TL,TJ)
168      IF(ZERO,EQ,0.0) GO TO 72

```

ORIGINAL PAGE IS  
OF POOR QUALITY

```

169      IF((YCRSS+ZERO).GT,360,0) GO TO 73
170      YCRSS=YCRSS+ZERO
171      GO TO 72
172      73 YCRSS=YCRSS-360,0+ZERO
173      72 IF(ABS(SSHT(1)).GT,EDIT1) GO TO 150
174      RESID=ABS(SSHT(2)-SSHT(1))
175      IF(RESID.GT,EDIT) GO TO 150
176      WRITE(SCR8) DATA
177      NDATA=NDATA+1
178      CRSNGS(NDATA,1)=DATA(2)
179      CRSNGS(NDATA,2)=DATA(1)
180      150 CONTINUE
181      DATA(1)=+1
182      WRITE(SCR8) DATA
183      200 CONTINUE
184      ENDFILE SCR8
185      WRITE(6,2000)
186      2000 FORMAT('1',83X,'SEAHT',////,36X,
187      1'LEAST SQUARES DETERMINATION OF SMOOTHED SEA SURFACE HEIGHTS',//,
188      237X,'CALCULATED AT INTERSECTING POINTS OF CROSSING REVOLUTIONS')
189      WRITE(6,3000) MINLAT,MAXLAT,MINLON,MAXLON
190      3000 FORMAT(////,557X,'CALIBRATION AREA',/,51X,'LATITUDE ',F8,2,
191      1' TO',F8,2,/,51X,'LONGITUDE ',F8,2,/, TO',F8,2)
192      WRITE(6,3001) NOPAR
193      3001 FORMAT('0',53X,'NO. OF PARAMETERS = ',I11)
194      WRITE(6,3003) NM
195      3003 FORMAT(//,50X,'NO. OF SOUTH-TO-NORTH REVS = ',I12)
196      WRITE(6,3002) NM
197      3002 FORMAT('0',49X,'NO. OF NORTH-TO-SOUTH REVS = ',I12)
198      WRITE(IOUT,1005)
199      DO 67 I=1,NM
200      INS=NSREV(I)/100000
201      INSSEG=(NSREV(I)-INS*100000)/10
202      67 WRITE(IOUT,1006) INS,INSSEG
203      WRITE(IOUT,1007)
204      DO 68 I=1,NM
205      ISN=SNREV(I)/100000
206      ISNSEG=(SNREV(I)-ISN*100000)/10
207      68 WRITE(IOUT,1005) ISN,INSSEG
208      1005 FORMAT('1',50X,'NORTH-TO-SOUTH REVOLUTIONS',/,54X,
209      1'REV NO      SEG NO',/)
210      1006 FORMAT(' ',54X,15,6X,15)

```

```

211 1007 FORMAT('D',50X,'SOUTH-TO-NORTH REVOLUTIONS',/,54X,
212 'REV NO',10X,'SEG NO',/).
213 WRITE(6,2999)
214 DO 3007 K=1,KNSTR
215 KNREV=KNSTR(K,1)/100000
216 KNSEG=(KNSTR(K,1)-KNREV*100000)/10
217 IF(KNSTR(K,2),EQ,1) WRITE(6,3004) KNREV,KNSEG
218 IF(KNSTR(K,2),EQ,2) WRITE(6,3005) KNREV,KNSEG
219 IF(KNSTR(K,2),EQ,3) WRITE(6,3006) KNREV,KNSEG
220 3007 CONTINUE
221 2999 FORMAT('1',47X,'*****CONSTRAINED REVS*****',///,43X,
222 'REV NO',25X,'SEG NO',10X,'TYPE OF CONSTRAINT',/,65X,'HEIGHT',3X,
223 'SLOPE',3X,'CURVATURE',/).
224 3006 FORMAT(43X,15,6X,15,10X,'*',7X,14,9X,'*')
225 3005 FORMAT(43X,15,4X,15,10X,'*',7X,14,9X,'*')
226 3004 FORMAT(43X,15,6X,15,10X,'*')
227 WRITE(IOUT,7000)
228 210 WRITE(IOUT,7001)
229 WRITE(IOUT,7002)
230 WRITE(IOUT,7004)
231 REWIND SQRB
232 READ(SQRB) T1
233 220 READ(SQRB,END=240) DATA
234 IF(DATA(1),EQ,MINUS) GO TO 220
235 I1=DATA(2)
236 I2=DATA(3)
237 DATA(1)=NSREV(I1)
238 DATA(2)=SNREV(I2)
239 INS=DATA(1)/100000
240 INSSEG=(DATA(1)-INS*100000)/10
241 ISN=DATA(2)/100000
242 ISNSEG=(DATA(2)-ISN*100000)/10
243 WRITE(IOUT,7003) INS,INSSEG,ISN,ISNSEG,DATA(3),DATA(4),DATA(5),
244 DATA(6),DATA(7),DATA(8)
245 GO TO 220
246 240 NPRINT=NPRINT+1
247 IF(NPRINT,GT,1) RETURN
248 300 NDELI(1)=0
249 NDELI(2)=0
250 II=1
251 I1=2
252 NLIM=NM

```

ORIGINAL PAGE IS  
OF POOR QUALITY

57345 01 03-16-77 16,999

```

253      330 DO 350 I=1,NLIM
254          IF(NUMBER(I, NONLEG(1,I)),NDELT(I)),NE,0) GO TO 350
*** 1457 DO LOOP INDEX I MAY NOT BE REDEFINED IN CALL OR ABNORMAL FUNCTION
255      C DETERMINE THE NUMBER OF CROSSINGS OF ITH NS(SN) ARC
256          NCROSS=0
257          DO 340 J=1,NDATA
258              IF(CRSNGS(J,I),NE,1) GO TO 340
259      C TEST TO SEE IF SN(SN) ARC DELETED.
260          IF(NUMBER(CRSNGS(J,I),NONLEG(1,I)),NDELT(I)),EQ,0)
261              ,NCROSS=NCROSS+1
262      340 IF(NCROSS,GE,NPAR) GO TO 350
263          IF(NCROSS,EQ,0) GO TO 345
264          IT=NSREV(I)
265          IF(IT,EQ,2) IT=SNREV(I)
266          IT=NUMBER(IT,KNSTR,IKNSTR)
267          IF(IT,EQ,0) GO TO 345
268          IT=(NCROSS+1)-KNSTR(IT,2)
269          IF(IT,GE,0) GO TO 350
270      345 NDELI(I)=NDELI(I)+1
271          NDELT(I)=NDELT(I)+1
272          J=NDELT(I)
273          NONLEG(J,I)=1
274      350 CONTINUE
275          II=II+1
276          I1=1
277          NLIM=NN
278          IF(II,LE,2) GO TO 330
279          IF(NDELI(1),GT,0,OR,NDELI(2),GT,0) GO TO 300
280          I2=MAX0(NM,NN)
281          DO 410 I=1,I2
282              DO 410 J=1,2
283      410 INTNOS(I,J) = 1
284          NLIM=NM
285          DO 420 I1=1,I2
286              ILIM=NDELT(I1)
287              IF(ILIM,EQ,0) GO TO 420
288              DO 415 I=1,NLIM
289      415 IF(NUMBER(I, NONLEG(1,I1),ILIM),NE,0) INTNOS(I,I1)=0
*** 1457 DO LOOP INDEX I MAY NOT BE REDEFINED IN CALL OR ABNORMAL FUNCTION
290      420 NLIM=NN
291          DO 430 I=1,NM
292          IF(INTNOS(I,1),EQ,0) GO TO 430

```

```

293      NONS=NONS+1
294      NSREV(NONS)=NSREV(I)
295      INTNOS(NONS,1)=INTNOS(I,1)
296 430 CONTINUE
297      DO 435 I=1,NN
298      IF(INTNOS(I,2).EQ.0) GO TO 435
299      NOSN=NOSN+1
300      SNREV(NOSN)=SNREV(I)
301      INTNOS(NOSN,2)=INTNOS(I,2)
302 435 CONTINUE
303      NOKNST=0
304      DO 480 I=1,IKNSTR
305      K=KNSTR(I,1)
306      IJ=NUMBER(K,NSREV,NONS)
307      IF(IJ.EQ.0) IJ=NUMBER(K,SNREV,NOSN)
308      IF(IJ.EQ.0) GO TO 480
309      NOKNST=NOKNST+1
310      DO 475 J=1,2
311 475 KNSTR(NOKNST,J)=KNSTR(I,J)
312 480 CONTINUE
313      IKNSTR=NOKNST
314      REWIND SCRB
315      WRITE(DATAP) NONS,NOSN,(NSREV(I),I=1,NONS),(SNREV(I),I=1,NOSN),
316      ((KNSTR(I,J),I=1,NOKNST),J=1,2)
317      READ(SCRB) T
318 510 NDATA=0
319 550 READ(SCRB,END=600) DATA
320      IF(DATA(1).EQ.NINUS) GO TO 590
321      DATA(1)=NUMBER(DATA(1),INTNOS(1,2),NOSN)
322      DATA(2)=NUMBER(DATA(2),INTNOS,NONS)
323      IF(ABS(SSHT(1)).GT.EDIT1) GO TO 550
324      NDATA=NDATA+1
325      WRITE(DATAP) DATA
326      GO TO 550
327 590 IF(NDATA.GT.0) WRITE(DATAP) DATA
328      GO TO 510
329 600 ENDFILE DATAP
330      SCRB=DATAP
331      WRITE(IOU,7000)
332      GO TO 210
333 6000 FORMAT('1',15X,'THE CONSTRAINED ARC',I7,'HAS BEEN DELETED')
334 7000 FORMAT('1',1,30X,'ARC CROSSING DATA INPUT FOR THIS RUN')

```



57345 01 03-16-77 16.999

```
335      7001 FORMAT('Q',7X,'REVOLUTION NO',12X,'CROSSING POINTS',6X,  
336      1'SMOOTHED SEA SURFACE HEIGHT',8X,'TIME FROM EPOCH')  
337      7002 FORMAT(' ',2X,'NORTH-SOUTH SOUTH-NORTH',5X,'LATITUDE LONGITUDE',  
338      24X,'NORTH-SOUTH SOUTH-NORTH',6X,'NORTH-SOUTH SOUTH-NORTH')  
339      7003 FORMAT(' ',2X,I5,' ',I5,2X,I5,' ',I5,3X,F10.5,1X,F10.5,3X,F10.5,  
340      ,3X,F10.5,5X,F10.5,4X,F10.5)  
341      7004 FORMAT(1H1,80X,'ARC CROSSING DATA USED FOR ADJUSTMENTS')  
342      7005 FORMAT(' ',8X,'(REV/SEG)',4X,'(REV/SEG)',6X,'(DEGREES)',1X,  
343      ,'(DEGREES)',6X,'(METERS)',5X,'(METERS)',8X,'(MINUTES)',4X,  
344      ,'(MINUTES)')  
345      END  
***H 1470 EQUALITY OR NON-EQUALITY COMPARISON MAY NOT BE MEANINGFUL IN LOGICAL IF EXPRESSIONS  
***H 7 MEMORY EXPANDED, USE $LIMITS OR CORE= OPTION FOR NEXT RUN
```

57345 01 03-16-77 17,004

```
1      CSELDEL
2      SUBROUTINE SELDEL(NOTPS,ITAPS,N,ARRAY,SELECT,NSEL)
3      INTEGER SELECT(50,2),ITAPS(1),NSEL(1)
4      DIMENSION ARRAY(1)
5      IST=1
6      ILIM=NOTPS
7      IF(N.EQ,0) GO TO 30
8      IST=NUMBER(N,ITAPS,NOTPS)
9      IF(IST.EQ,0) RETURN
10     25 ILIM=IST
11     30 DO 50 IT=IST,ILIM
12         K=NSEL(IT)
13         DO 40 J=1,32
14             ISEL=ARRAY(J)*100000,0+ARRAY(J*1)*1000+0,1
15             IF(ISEL,EQ,0) GO TO 40
16             K=K+1
17             SELECT(K,IT)=ISEL
18     40 CONTINUE
19         NSEL(IT)=K
20     50 CONTINUE
21     RETURN
22     END
```

57345 01 03-16-77 17.005

```

1  GCROSS
2  SUBROUTINE BCROSS(XCROSS,YCROSS,ANLATM,ANLNGM,AXLATM,AXLNGM,ENLATN,
3  ,ENLNGM,EXLATN,EXLNGM,INDC)
4  COMMON/ALT/ NI,ARRAY(4,1000)INJ,ARRY(4,1000)
5  ENLATM=AXLATM
6  ENLNGM=AXLNGM
7  EXLATM=ANLATM
8  EXLNGM=ANLNGM
9  INDC=0
10 IF(EXLATM.EQ.ENLATN.AND.EXLNGM.EQ.ENLNGM) GO TO 501
11 IF(EXLATN.EQ.ENLATM.AND.EXLNGM.EQ.ENLNGM) GO TO 500
12 IF(ENLATM.LT.EXLATN) GO TO 10
13 GO TO 20
14 5 IF(EXLATM.GT.ENLATN) 30 TO 30
15 GO TO 40
16 10 DO 11 I=1,NI-1
17 11 IF(ENLATM.GE.ARRY(2,I).AND.ENLATM.LE.ARRY(2,I+1))
18 ,GO TO 15
19 GO TO 99
20 15 CALL YFIND(ENLATM,ARRY(2,I),ARRY(2,I+1),ARRY(3,I),ARRY(3,I+1),Y)
21 IF(Y.GT.ENLNGM) GO TO 99
22 GO TO 5
23 20 DO 21 I=1,NI-1
24 21 IF(EXLATN.LE.ARRAY(2,I).AND.EXLATN.GE.ARRAY(2,I+1))
25 ,GO TO 25
26 GO TO 99
27 25 CALL YEIND(EXLATN,ARRAY(2,I),ARRAY(2,I+1),ARRY(3,I),ARRY(3,I+1),
28 ,Y)
29 IF(Y.LT.EXLNGM) GO TO 99
30 GO TO 5
31 30 DO 31 I=1,NI-1
32 31 IF(EXLATM.GE.ARRY(2,I).AND.EXLATM.LE.ARRY(2,I+1)) GO TO 35
33 GO TO 99
34 35 CALL YFIND(EXLATM,ARRY(2,I),ARRY(2,I+1),ARRY(3,I),ARRY(3,I+1),Y)
35 IF(Y.LT.EXLNGM) GO TO 99
36 GO TO 6
37 40 DO 41 I=1,NI-1
38 41 IF(ENLATN.LE.ARRAY(2,I).AND.ENLATN.GE.ARRAY(2,I+1)) GO TO 45
39 GO TO 99
40 45 CALL YEIND(ENLATN,ARRAY(2,I),ARRY(2,I+1),ARRY(3,I),ARRY(3,I+1),
41 ,Y)
42 IF(Y.GT.ENLNGM) GO TO 99

```

57385 01 03-16-77 17,005

68

```

43      6 KOUNT=0
44      1 SLPNS=(ENLNGM-EXLNGM)/(ENLATM-EXLATM)
45      SLPNS=(ENLNGN-EXLNGN)/(ENLATN-EXLATN)
46      CYS=(ENLNGM*SLPNS+ENLATM)
47      CSN=(ENLNGN*SLPNS+ENLATN)
48      XINT=(CSN-CYS)/(SLPNS-SLPNS)
49      YINT=(SLPNS*CSN-SLPNS*CSN)/(SLPNS-SLPNS)
50      NOLAT=0
51      KOUNT=KOUNT+1
52      IF(KOUNT.GT.10) GO TO 99
53      DO 100 I=1,N1-1
54      100 IF(YINT.LE.ARRAY(3,I).AND.YINT.GE.ARRAY(3,I+1)) GO TO 101
55      IF(KOUNT.GT.10) GO TO 99
56      NOLAT=1
57      GO TO 199
58      101 CALL YFIND(YINT,ARRAY(3,I),ARRAY(3,I+1),ARRAY(2,I),ARRAY(2,I+1),
59      XNS)
60      199 DO 200 I=1,N1-1
61      200 IF(YINT.LE.ARRAY(3,I).AND.YINT.GE.ARRAY(3,I+1)) GO TO 201
62      IF(KOUNT.GT.10) GO TO 99
63      NOLAT=2
64      GO TO 299
65      201 CALL YFIND(YINT,ARRAY(3,I),ARRAY(3,I+1),ARRAY(2,I),ARRAY(2,I+1),XNS)
66      299 IF(NOLAT.EQ.1) GO TO 305
67      IF(NOLAT.EQ.2) GO TO 310
68      IF(ABS(XNS-XSN).LE.0.0001) GO TO 400
69      IF(XNS.LT.XSN) GO TO 300
70      ENLATN=XSN
71      ENLNGN=YINT
72      ENLATM=XNS
73      ENLNGM=YINT
74      GO TO 1
75      300 EXLATN=XSN
76      EXLNGN=YINT
77      EXLATM=XNS
78      EXLNGM=YINT
79      GO TO 1
80      305 IF(XSN.GE.XINT) GO TO 307
81      ENLATN=XSN
82      ENLNGN=YINT
83      GO TO 1
84      307 EXLATN=XSN

```

ORIGINAL PAGE IS  
OF POOR QUALITY

57345 01 03-16-77 17.009

```

      85      EXLNGN=YINT
      86      GO TO 1
      87      310 IF(XNS.GE.XTNT) GO TO 311
      88      EYLATM=XNS
      89      EXLNGM=YINT
      90      GO TO 1
      91      311 ENLATM=XNS
      92      ENLNGM=YINT
      93      GO TO 1
      94      400 XCROSS=(XNS#XSN)/2.0
      95      YCROSS=YINT
      96      RETURN
      97      99 INDC#1
      98      RETURN
      99      500 XCROSS=EXLATM
     100      YCROSS=EXLNGN
     101      RETURN
     102      501 XCROSS=EXLATM
     103      YCROSS=EXLNGM
     104      RETURN
     105      END
06 ***XW 1475 EQUALITY OR NON-EQUALITY COMPARISON MAY NOT BE MEANINGFUL IN LOGICAL IF EXPRESSIONS
```

57345 01 03-16-77 17.007

```
1      SUBROUTINE XFIND(X,TWOI,TWOI1,THREEI,THREEI1,THREE)
2      DX=(X-TWOI)/Z(TWOI1-TWOI)
3      DY=THREEI1-THREEI
4      ADDTOY=DX*DY
5      THREE=THREEI+ADDTOTY
6      RETURN
7      END
```

91

ORIGINAL PAGE IS  
OF POOR QUALITY

```

1      CGHTIM
2      SUBROUTINE BHTIM(XCROSS,YCROSS,GJ,TI,TJ)
3      COMMON/ALT/N1,ARRAY(4,1000),NJ=ARRAY(8,1000)
4      IF(ARRAY(2,N1).EQ.XCROSS) GO TO 57
5      IF(ARRAY(2,1).EQ.XCROSS) GO TO 58
6      NE = N1-1
7      DO 49 IN=1,NE
8      IF((ARRAY(2,IN)-XCROSS)*(ARRAY(2,IN+1)-XCROSS).LT.0.) GO TO 55
9      49 CONTINUE
10     55 A=XCROSS*ARRAY(2,IN)
11     B=ARRAY(2,IN+1)-ARRAY(2,IN)
12     C=ARRAY(4,IN+1)-ARRAY(4,IN)
13     D=ARRAY(1,IN+1)-ARRAY(1,IN)
14     GI=((A+C)/B)*ARRAY(4,IN)
15     TI=((A+D)/B)*ARRAY(1,IN)
16     NA = NJ-1
17     DO 53 IN=1,NA
18     IF((ARRY(2,IN)-XCROSS)*(ARRY(2,IN+1)-XCROSS).LT.0.) GO TO 42
19     53 CONTINUE
20     42 A=XCROSS*ARRY(2,IN)
21     B=ARRY(2,IN+1)-ARRY(2,IN)
22     C=ARRY(4,IN+1)-ARRY(4,IN)
23     D=ARRY(1,IN+1)-ARRY(1,IN)
24     GJ=(A+C/B)*ARRY(4,IN)
25     TJ=((A+D)/B)*ARRY(1,IN)
26     RETURN
27     57 GI=ARRAY(4,N1)
28     TI=ARRAY(1,N1)
29     GJ=GJ
30     TJ=TJ
31     RETURN
32     58 GI=ARRAY(4,1)
33     TI=ARRAY(1,1)
34     GJ=GJ
35     TJ=TJ
36     RETURN
37     END

```

\*\*\* 1470 EQUALITY OR NON-EQUALITY COMPARISON MAY NOT BE MEANINGFUL IN LOGICAL IF EXPRESSIONS





```

1      CSOLVE
2      SUBROUTINE SOLVE(IADDR,SNREV,NSREV,SUM1,SUM2,DELTA,BBIAS,KNSTR,
3      ARRAY)
4      DIMENSION ABRAY(4,1)
5      DIMENSION SIGMA(2),BBIAS(1),DATA(8),SSHT(5)
6      COMMON= SOUTH - NORTH
7      DOUBLE PRECISION SUM1(1),SUM2(1),DELTA(1),ARCPAR(6),COMPAR(3)
8      INTEGER SNTAPE
9      INTEGER ARCNOS(6),GTAP,SCRB,SNREV(1),NSREV(1),IADDR(1),KNSTR(1)
10     INTEGER Q,R
11     INTEGER REVND,DATAP,DOUT
12     INTEGER SCRB
13     INTEGER DUM1,DUM2,DUM3
14     DATA DUM1/0/,DUM2/0/,DUM3/0/
15     COMMON/TAPES/INTP,IOUT,GTAP,NSTAPE,SNTAPE,SCRB,SCRC,DATAP,DOUT
16     COMMON/KONTBL/NOPAR,NQNS,NOSN,IKNSTR,EDIT,MAX
17     EQUIVALENCE (ISN,DATA(1)),(INS,DATA(2))
18     DATA ARCNOS/1,2,3,3*0/
19     DATA SIGMA/2*1,0/
20     DATA AVE/0.0/,SDEV/0.0/,KOUNT/0/
21     DATA INTPOS/0/
22     WRITE(IOUT,2001) (IADDR(I),I=1*8)
23     2001 FORMAT(/////*1X,'STARTING ADDRESSES OF ARRAYS',//,3X,'SNREV',5X,
24     ,012,/,3X,'NSREV',5X,012,/,3X,'SUM1',6X,012,/,3X,'SUM2',6X,012,/,
25     ,3X,'DELTA',5X,012,/,3X,'BBIAS',5X,012,/,3X,'KNSTR',5X,012,
26     ,/,3X,'ARRAY',5X,012)
27     RETURN
28     ENTRY SOLVE
29     JTAP=19
30     REWIND SCRB
31     IJK=2*IKNSTR
32     READ(SCRB) I1,I2,(NSREV(I),I=1,NQNS),(SNREV(I),I=1,NOSN),
33     ,(KNSTR(I),I=1,IJK)
34     NDIM=NOPAR*(NOSN+1)
35     CALL CLEAR(BBIAS,VDIM)
36     CALL ESTIM1(SUM1,SUM2,DELTA,BBIAS,ARCNOS,ARCPAR,NOPAR,NOSN)
37     ARCPAR(1)=1.000
38     COMPAR(1)=-1.000
39     100 READ(SCRB,END=200) DATA
40     IF(ISN.LT.0) GO TO 150
41     IARC=INS
42     ARCPAR(2)=DATA(7)

```

43 ARCPAR(3)=DATA(7)\*#2  
 44 COMPAR(2)=-DATA(8)  
 45 COMPAR(3)=-DATA(8)\*#2  
 46 RESID=DATA(5)-DATA(6)  
 47 IF(ABS(RESID),LE,EDIT)  
 48 CALL ESTIM(NOPAR+ISN,COMPAR,SIGMA,RESID)  
 49 GO TO 100  
 50 150 ICON=0  
 51 IJK=NUMBER(NSREV(IARC),KNSTR,IKNSTR)  
 52 IF(IJK.GT.0) ICON=KNSTR(IJK+IKNSTR)  
 53 CALL ESTIMA(ICON)  
 54 CALL CLEAR(BBIAS,NOPAR)  
 55 GO TO 100  
 56 200 CALL ESTIMQ(SNREV,KNSTR,IKNSTR)  
 57 DO 500 KSN=1,NOSN  
 58 REWIND SQRB  
 59 READ(SQRB) T1  
 60 IBC=NOPAR+1  
 61 IF(KSN.NB,1) GO TO 501  
 62 WRITE(IOUT,11)  
 63 WRITE(GTAP,15)  
 64 WRITE(JTAP,15)  
 65 WRITE(GTAP,16)  
 66 WRITE(JTAP,16)  
 67 WRITE(GTAP,17)  
 68 WRITE(JTAP,20)  
 69 WRITE(GTAP,19)  
 70 WRITE(JTAP,19)  
 71 REWIND NSTAPE  
 72 501 CONTINUE  
 73 DO 400 IARC=1,NONS  
 74 CALL URDATE  
 75 IF(KSN.NB,1) GO TO 502  
 76 IREV=NSREV(IARC)/100000  
 77 ISEG=(NSREV(IARC)-IREV\*100000)/10  
 78 WRITE(IOUT,1010) IREV,ISEG,(BBIAS(I),I=1,NOPAR)  
 79 205 READ(NSTAPE) REVNO,NI,((ARRAY(C,R),C=1,4),R=1,NI)  
 80 IF(REVNO.NE#NSREV(IARC)) GO TO 205  
 81 WRITE(DOUT) DUM1,DUM2,NI,ISEG,IREV  
 82 DO 207 K=1,NI  
 83 ARRAY(1,K)=ARRAY(1,K)\*60000.  
 84 ARRAY(2,K)=ARRAY(2,K)\*3600000.

```

85      ARRAY(3,K)=ARRAY(3,K)*3600000,
86      ITIME=ARRAY(1,K)
87      ILAT=ARRAY(2,K)
88      ILON=ARRAY(3,K)
89      GO TO (208,209,210),NOPAR
90      208 ARRAY(4,K)=ARRAY(4,K)=BBIAS(1)
91      GO TO 206
92      209 ARRAY(4,K)=ARRAY(4,K)=(BBIAS(2)*ARRAY(1,K)+BBIAS(1))
93      GO TO 206
94      210 XBBIAS=BBIAS(3)*ARRAY(1,K)**2+BBIAS(2)*ARRAY(1,K)+BBIAS(1)
95      ARRAY(4,K)=ARRAY(4,K)=XBBIAS
96      206 ARRAY(4,K)=ARRAY(4,K)*1000000,
97      ISEAHT=ARRAY(4,K)
98      207 WRITE(DOUT) ITIME,ILAT,ILON,ISEAHT,DUM3
99      ENDFILE DOUT
100     CONTINUE
101     300 READ(SCRB,END=410) DATA
102     IF(ISN.EQ.-1) GO TO 400
103     IF(KSN.NE.1.AND.ISN.NE.KSN) GO TO 300
104     I2=IBC+NOPAR*(ISN-1)
105     SSHT(1)=DATA(5)
106     SSHT(2)=DATA(6)
107     DO 310 I=1,NOPAR
108     SSHT(1)=SSHT(1)-BBIAS(I)*DATA(7)**(I-1)
109     SSHT(2)=SSHT(2)-BBIAS(I2)*DATA(8)**(I-1)
110     I2=I2+1
111     310 CONTINUE
112     SSHT(3)=(SSHT(1)+SSHT(2))/2,0
113     SSHT(4)=SSHT(1)-SSHT(3)
114     SSHT(5)=SSHT(2)-SSHT(3)
115     IF(ABS(DATA(5)-DATA(6)),GT,EDIT) GO TO 330
116     AVE=AVE+SSHT(4)
117     SDEV=SDEV+SSHT(4)**2
118     KOUNT=KOUNT+1
119     330 IF(KSN.EQ.1) WRITE(UTAP,1000)NSREV(ISN)/100000,SHREV(ISN)/100000,
120     ,DATA(3),DATA(4),BBIAS(1),BBIAS(I2-NOPAR),DATA(5),DATA(6),
121     ,(SSHT(K),K=1,4)
122     IF(ISN.EQ.KSN)WRITE(UTAP,1000)SNREV(1SN)/100000,NSREV(ISN)/100000,
123     ,DATA(3),DATA(4),BBIAS(I2-NOPAR),BBIAS(1),DATA(6),DATA(5),SSHT(2),
124     ,SSHT(1),SSHT(3),SSHT(5)
125     GO TO 300
126     400 CONTINUE

```

ORIGINAL PAGE IS  
OF POOR QUALITY

```

127 410 CONTINUE
128 500 REWIND SQRC
129 WRITE(IOUT,28)
130 REWIND SNTAPE
131 DO 420 I=1,NOSN
132 IE=IBC+NOPAR-1
133 IREV=SNREV(I)/100000
134 ISEG=(SNREV(I)-IREV*100000)/10
135 WRITE(IOUT,2010) IREV,ISEG,(BBIAS(J),J=IBC,IE)
136 405 READ(SNTAPE) REVNO,NJ,((ARRAY(C,R),C=1,4),R=1,NJ)
137 IF(REVNO.NE.SNREV(I)) GO TO 405
138 WRITE(DOUT) DUM1,DUM2,NJ,ISEG,IREV
139 DO 407 K=1,NJ
140 ARRAY(1,K)=ARRAY(1,K)*60000,
141 ARRAY(2,K)=ARRAY(2,K)*3600000,
142 ARRAY(3,K)=ARRAY(3,K)*3600000,
143 ITIME=ARRAY(1,K)
144 ILAT=ARRAY(2,K)
145 ILON=ARRAY(3,K)
146 GO TO (408,409,411),NOPAR
147 408 ARRAY(4,K)=ARRAY(4,K)-BBIAS(IBC)
148 GO TO 406
149 409 ARRAY(4,K)=ARRAY(4,K)-(BBIAS(IBC+1)*ARRAY(1,K)+BBIAS(IBC))
150 GO TO 406
151 411 YBIAS=BBIAS(IBC+2)*ARRAY(1,K)+BBIAS(IBC+1)*ARRAY(1,K)
152 YBIAS=YBIAS-BBIAS(IBC)
153 ARRAY(4,K)=ARRAY(4,K)-YBIAS
154 406 ARRAY(4,K)=ARRAY(4,K)*1000000,
155 ISEAHT=ARRAY(4,K)
156 407 WRITE(DOUT) ITIME,ILAT,ILON,ISEAHT,DUM3
157 ENDFILE DOUT
158 IBC=IBC+NOPAR
159 420 CONTINUE
160 AVE=AVE/KOUNT
161 SDEV=SDEV-AVE**2
162 SDEV=SDEV/KOUNT
163 WRITE(GTAP,28) AVE
164 28 FORMAT('Q',1,MEAN OF RESIDUALS',5X,F10.5)
165 WRITE(GTAP,29) SDEV
166 29 FORMAT('Q',1,STANDARD DEVIATION',5X,F10.5)
167 11 FORMAT('11',17X,'*****BIASES*****',/,16X,'NORTH-TO-SOUTH REVS',/,
168 ,IREV NO',5X,'SEG NO',11X,'COEFFICIENTS')

```

936 # # # # W

```

7 MEMORY EXPANDED, USE $LIMITS OR CORE= OPTION FOR NEXT RUN

```



```

1      LBL      CHARLY,SEAH7 SUBROUTINE CHARLY      CHARLY01
2      TTL      SUBROUTINE CHARLY - DYNAMIC MEMORY ALLOCATOR      CHARLY02
3      ***** START OF DOCUMENTATION COMMENT CARDS *****      CHARLY03
4      #
5      #      PROGRAM TITLE - SUBROUTINE CHARLY      #CHARLY04
6      #      PROGRAM NO.      - 112293      #CHARLY05
7      #      WRITTEN BY DAN CHIN (WOLF RESEARCH AND DEVELOPMENT)      #CHARLY06
8      #      REWRITTEN BY TOM HARMON (NASA WOLLOPS-AMS) 1/74      #CHARLY07
9      #      MODIFIED BY TOM NORTHAM (WRDC) 5/74, 6/74      #CHARLY08
10     #
11     #      HARDWARE/SOFTWARE SUMMARY      #CHARLY09
12     #
13     #      COMPUTER REQUIRED - HONEYWELL 600/6000 SERIES      #CHARLY10
14     #      SYSTEM EXECUTIVE - GECOS III      #CHARLY11
15     #      PROGRAM LANGUAGE - GMAP      #CHARLY12
16     #      PERIPHERALS - NONE      #CHARLY13
17     #
18     #      PURPOSE      #CHARLY14
19     #
20     #      THIS SUBROUTINE DYNAMICALLY ALLOCATES ARRAY STORAGE FOR USE      #CHARLY15
21     #      WITH THE SEAH7 PROGRAM.      #CHARLY16
22     #
23     #      METHOD      #CHARLY17
24     #
25     #      WORD 31 (DECIMAL) IN THE SLAVE PROGRAM PREFIX IS SCANNED      #CHARLY18
26     #      TO FIND THE LOCATION OF AVAILABLE MEMORY FOR ARRAY ALLOCATION.      #CHARLY19
27     #      IF SUFFICIENT MEMORY ISN'T AVAILABLE, THEN AN ATTEMPT TO      #CHARLY20
28     #      GET MORE MEMORY IS MADE, IF GCOS DENIES THE REQUEST,      #CHARLY21
29     #      THEN CHARLY RETURNS TO THE NON STANDARD ERROR EXIT,      #CHARLY22
30     #      OTHERWISE, THE ARRAY LOCATIONS ARE STORED INTO THE SOLVEI      #CHARLY23
31     #      CALLING SEQUENCE AND A CALL TO SOLVEI IS EXECUTED.      #CHARLY24
32     #
33     #      CALLING SEQUENCE      #CHARLY25
34     #
35     #      CALL CHARLY(KOREB,IMORE,NCORE,ICORE,KOREG,$NNN)      #CHARLY26
36     #
37     #      KOREB = THE AMOUNT OF CORE THAT MUST BE AVAILABLE FOR      #CHARLY27
38     #      BUFFERS AFTER CHARLY HAS BEEN CALLED,      #CHARLY28
39     #      IMORE = THE SUM OF ARRAY SIZES,      #CHARLY29
40     #      NCORE = NUMBER OF ARRAYS FOR WHICH CORE MUST BE      #CHARLY30
41     #      ALLOCATED,      #CHARLY31
42     #      ICORE = NUMBER OF WORDS OF CORE REQUIRED BY EACH ARRAY,      #CHARLY32

```

```

43 *          KOREG = THE AMOUNT OF CORE LEFT IN USER JOB SEGMENT *CHARLY43
44 *          IF POSITIVE, THE AMOUNT OF CORE TO BE GEMORE-D *CHARLY44
45 *          IF NEGATIVE, *CHARLY45
46 *          $NNN = RETURN WHEN CORE ALLOCATION NOT SUCCESSFUL *CHARLY46
47 * *CHARLY47
48 * *CHARLY48
49 * RETURNS *CHARLY49
50 * *CHARLY50
51 *          NORMAL ONLY (TERMINATION OCCURS IN CONSOL *CHARLY51
52 *          ON INSUEFICIENT MEMORY AVAILABLE) *CHARLY52
53 * *CHARLY53
54 * INPUT *CHARLY54
55 * *CHARLY55
56 *          VIA CALLING SEQUENCE *CHARLY56
57 * *CHARLY57
58 * OUTPUT *CHARLY58
59 * *CHARLY59
60 *          CHARLY GENERATES A SIMULATED CALL SOLVEI(ARG1,ARG2,...) *CHARLY60
61 *          WHERE ARG1 POINTS TO THE ADDRESS OF ARG2, AND ARG2 THRU ARGN *CHARLY61
62 *          CONTAIN THE ADDRESSES OF THE DYNAMICALLY ALLOCATED ARRAYS. *CHARLY62
63 * *CHARLY63
64 * SUBPROGRAMS REQUIRED *CHARLY64
65 * *CHARLY65
66 *          SOLVEI *CHARLY66
67 * *CHARLY67
68 * CALLED BY *CHARLY68
69 * *CHARLY69
70 *          SEAMT MAIN PROGRAM *CHARLY70
71 * *CHARLY71
72 * EXTERNAL REFERENCES *CHARLY72
73 * *CHARLY73
74 *          NONE *CHARLY74
75 * BIBLIOGRAPHY *CHARLY75
76 * *CHARLY76
77 * *CHARLY77
78 * *CHARLY78
79 * *CHARLY79
80 * ***** END OF DOCUMENTATION COMMENT CARDS *****CHARLY80

```



000000	000000	02	CHARLY SAVE					CHARLY82
000002	7200	41	000	83	LXLQ	2,1*	ACCESS KOREP	CHARLY83
000044	7400	00	010	84	STXQ	X	STORE IN UPPER HALF OF INSTR AT LOC X	CHARLY84
000007	5500	00	010	85	SBAR	**1		CHARLY85
000000	2350	07	000	86	LDA	**DL	GET BAR IN AL	CHARLY86
000777	3750	07	000	87	ANA	±0777,DL	NO. OF 512 WORD BLOCKS	CHARLY87
000011	7350	00	000	88	ALS	9	MULTIPLY BY 512	CHARLY88
000001	1750	07	000	89	SBA	1,DL	UPPER CORE ADDRESS	CHARLY89
000037	7510	07	000	90	STCA	31,07		CHARLY90
000004	2350	31	000	91	LDA	4,1*	NO. OF ELEMENTS	CHARLY91
000006	7350	00	000	92	ALS	6		CHARLY92
000153	7510	06	010	93	STCA	OTTALY+1,06	INITIALIZE WORKING TALLY WORD	CHARLY93
000153	2350	00	010	94	LDA	OTTALY+1		CHARLY94
000152	7550	00	010	95	STA	OTTALY		CHARLY95
000005	6200	31	000	96	EAXQ	5,1*	ARRAY ADDRESS	CHARLY96
000051	7400	00	010	97	STXQ	INTALY		CHARLY97
Y 30	CHARLY02							
000037	2350	00	000	98	LDA	31		CHARLY98
777777	3750	03	000	99	ANA	±1,DU	GET LOWER MEMORY ADDRESS IN AU	CHARLY99
000001	0350	03	000	100	ADLA	1,DU	MAKE ADDRESS EVEN	CHARLY00
777776	3750	03	000	101	ANA	±0777776,DU		CHARLY01
000152	7550	56	010	102	STA	OTTALY, ID	AND STORE INTO CALLING SEQUENCE	CHARLY02
000002	6070	04	000	103	TTF	2,IC	CHECK FOR TALLY RUNDOUT	CHARLY03
000036	7100	00	010	104	TRA	CKMEM	YES	CHARLY04
000151	7200	56	010	105	LXLQ	INTALY, ID	SIZE OF ARRAY	CHARLY05
000034	7400	00	010	106	STXQ	**1		CHARLY06
000000	0350	03	000	107	ADLA	**DU		CHARLY07
000025	7100	00	010	108	TRA	AGAIN		CHARLY08
000151	7200	56	010	109	CKMEM	LXLQ	SIZE OF LAST ARRAY	CHARLY09
000040	7400	00	010	110	STXQ	**1		CHARLY10
000000	0350	03	000	111	ADLA	**DU		CHARLY11
000037	7510	70	000	112	STCA	31,70	UPDATE LOWER LIMIT	CHARLY12
000037	7200	00	000	113	LXLQ	31	UPPER MEMORY LIMIT	CHARLY13
000037	1600	00	000	114	SBXQ	31	LOWER MEMORY LIMIT	CHARLY14
000000	1600	03	000	115	SBXQ	**DU		CHARLY15
000000	6350	10	000	116	EAA	0.0	GET X0 IN AU	CHARLY16
Y CARD	CHARLY03							
000022	7310	00	000	117	ARS	18	SHIFT AU TO AL W SIGN SET	CHARLY17

ORIGINAL PAGE IS  
OF POOR QUALITY

-77 17.017

## SUBROUTINE CHARLY - DYNAMIC MEMORY ALLOCATOR

PAGE

5

00006 7550 31	000	118	STA	8,10		CHARLY18
00154 6050 00	010	119	TPL	PCALL		CHARLY19
00000 5310 00	000	120	GMORE	NEG	WE HAVE ENOUGH MEMORY	CHARLY20
01777 0350 07	000	121	ADLA	1023,DL	MAKE DIFFERENCE POSITIVE	CHARLY21
00012 7710 00	000	122	ARL	10	ROUND TO NEAREST 1K	CHARLY22
00150 7550 00	010	123	STA	MEMSIZ		CHARLY23
00061 7510 07	010	124	STCA	MME*1.07	STORE K REQD IN MME ZERO WORD	CHARLY24
00012 7350 00	000	125	ALS	10		CHARLY25
00037 0550 00	000	126	ASA	31	UPDATE UPPER MEMORY LIMIT	CHARLY26
00011 0010 00	000	127	MME	GMORE	ASK FOR MORE MEMORY	CHARLY27
00000 000000	000	128	ZERQ	0,**		CHARLY28
00002 7100 04	000	129	TRA	2,IC	DENIAL	CHARLY29
00135 7100 00	010	130	TRA	PCALL1		CHARLY30
00065 7100 00	010	131	DENIAL	TRA		CHARLY31
0000701000	030	132	SMESG1	CALL	CONSOL(MEMSIZ,IREPLY)DENRET	CHARLY32
00073710000	010					
00217000204	010					
00150000000	010					
CARD CHARLY04						
0000000000	010					
00100 710000	010					
001 2340 00	010	133	SZN	IREPLY		CHARLY33
00131 6000 00	010	134	TZE	DENRET		CHARLY34
00143 0540 00	010	135	AQS	GMRIND		CHARLY35
0000701000	030	136	CALL	CLKTIM(TIMZRO)		CHARLY36
00102710000	010					
00217000210	010					
00145000000	010					
00130 2350 00	010	137	LDA	DENAL1		CHARLY37
00064 7550 00	010	138	STA	DENIAL		CHARLY38
00060 7100 00	010	139	TRA	MME		CHARLY39
0000701000	030	140	SMESG2	CALL	CLKTIM(TIME)	CHARLY40
00111710000	010					
00217000214	010					
00146000000	010					
00146 2350 00	010	141	LDA	TIME		CHARLY41
00145 1750 00	010	142	SBA	TIMZRO		CHARLY42
00036 1150 07	000	143	CMPI	30,DL		CHARLY43
CARD CHARLY05						
00060 7100 00	010	144	TRA	MME		CHARLY44
0000701000	030	145	CALL	BONNES		CHARLY45
00120710000	010					

```

00217000221 010
10000701000 030 .146 .CALL .CLKTIM(TIMZRO)
00124710000 010
00217000222 010
00145000000 010
00144 0540 00 010 147 AQS CLKCNT
00144 2340 00 010 148 SZN CLKCNT
00131 6000 00 010 149 TZE DENRET
00160 7100 00 010 150 TRA MME
00105 7100 00 010 151 DENAL1 TRA SMESG2
000132 152 DENRET RETURN CHARLY,1
00217221051 010
00001161003 000
00217741000 010
00001710000 010
00143 2340 00 010 153 FCALL1 SZN GMRIND
00154 6000 00 010 154 TZE FCALL
CARD CHARLY06
20000701000 030 155 CALL CONGR1
00000710000 010
000007000233 010
00154 7100 00 010 156 TRA FCALL
00000000000 000 157 GMRIND DEC 0
777777777766 000 158 CLKCNT DEC -10
000145 159 TIMZRO BSS 1
000146 160 TIME BSS 1
000147 161 IREPLY BSS 1
000158 162 MEMSIZ BSS 1
00000 0000 00 000 163 INTALY TALLY **,0
00000 0000 00 000 164 OTTALY TALLY **,**
00160 0000 00 010 165 TALLY FCALL+4,**
166 SYMREF SOLVE!
50000 7010 00 030 167 FCALL TSX1 SOLVE!
00216 7100 00 010 168 TRA NCALL
00217 000000 010 169 ZERO ?E,L..
00160 0000 00 010 170 ARG **1
000165 171 BSS 30
00001710000 010 172 VCALL RETURN CHARLY

```

INPUT TALLY WORD  
WORKING TALLY WORD

MAXIMUM OF 30 ARRAYS

CHARLY46

CHARLY47

CHARLY48

CHARLY49

CHARLY50

CHARLY51

CHARLY52

CHARLY53

CHARLY54

CHARLY55

CHARLY56

CHARLY57

CHARLY58

CHARLY59

CHARLY60

CHARLY61

CHARLY62

CHARLY63

CHARLY64

CHARLY65

CHARLY66

CHARLY67

CHARLY68

CHARLY69

CHARLY70

CHARLY71

CHARLY72

AGE

00000000000 000

ORIGINAL PAGE IS  
OF POOR QUALITY

57345 03 03-16-77 17,017 SUBROUTINE CHARLY - DYNAMIC MEMORY ALLOCATOR

000220 233021514370 000  
END OF BINARY CARD CHARLY07

173 END

222 IS THE NEXT AVAILABLE LOCATION,  
GMAP VERSION/ASSEMBLY DATES JMPA 730601/052373 JMPB 730601/052373 JMPD 730601/052373  
THERE WERE NO WARNING FLAGS IN THE ABOVE ASSEMBLY

ORIGINAL PAGE IS  
OF POOR QUALITY

```

1      CCONSOL
2      SUBROUTINE CONSOL(MEMSIZE,IREPLY,*)
3      DIMENSION MES(10),MES0(11),MES1(11),MES2(8),MES21(9),MES3(9),
4      MES5(7)
5      CHARACTER*6 MES,MES0,MES1,MES2,MES21,MES3,MES5
6      CHARACTER*6 CONSLW,NANS1,NANS2,NANS3,NANS4
7      CHARACTER*6 NANS5,NANS6,NANS7,NANS8
8      CHARACTER*6 IZERO
9      CHARACTER*6 NREPLY
10     DATA MES/50HPLEASE SET OTHER JOBS URGC TO 00 SO THEY WILL SWAP OUT
11     DATA STATEMENT: VARIABLE LIST EXCEEDS LITERAL LIST
12     DATA MES0/6HHTYPE ** YES ** AND SET ALL OTHER ** URGC ** TO 00 OR
13     DATA STATEMENT: VARIABLE LIST EXCEEDS LITERAL LIST
14     DATA MES1/6HGEODYN NEEDS K ADDITIONAL CORE FOR A TOTAL OF
15     DATA STATEMENT: VARIABLE LIST EXCEEDS LITERAL LIST
16     DATA MES2/4HHTYPE YES AND TEMPORARILY SWAP OTHER JOBS OUT,,, /
17     DATA STATEMENT: VARIABLE LIST EXCEEDS LITERAL LIST
18     DATA MES21/54H BY SETTING ALL OTHER URGENCIES TO ZERO,,, OR.,
19     DATA STATEMENT: VARIABLE LIST EXCEEDS LITERAL LIST
20     DATA MES3/5HHTYPE NO AND GEODYN WILL STOP EXECUTION AND ENDJOB,
21     DATA STATEMENT: VARIABLE LIST EXCEEDS LITERAL LIST
22     DATA MES5/54H**GEODYN** GOT THE CORE IT NEEDED,,, THANK YOU,
23     DATA STATEMENT: VARIABLE LIST EXCEEDS LITERAL LIST
24     DATA CONSLW/6H00000T//,NANS1/6HYES  X,NANS2/6HY
25     DATA NANS3/6HNO /,NANS4/6HN /
26     DATA NANS5/6HYES000/,NANS6/6HY00000/,NANS7/6HN00000/,NANS8/6HN0000
27     DATA IZERO/8H0000000/
28     NREPLY=IZERO
29     CALL MEMSIZE(MTSIZE)
30     MTSIZE=MTSIZE+MEMSIZE
31     PRINT 100,MEMSIZE,MTSIZE
32     100 FORMAT(1X,012,1X,012)
33     IF(MTSIZE.GT.80.OR,MEMSIZE.GT.25) GO TO 15
34     ENCODE (MES1(3),10) MEMSIZE
35     ENCODE (MES1(10),10) MTSIZE

```

```

CONSOL01
CONSOL02
CONSOL03
CONSOL04
CONSOL05
CONSOL06
CONSOL07
CONSOL08
CONSOL09
CONSOL10
CONSOL11
CONSOL12
CONSOL13
CONSOL14
CONSOL15
CONSOL16
CONSOL17
CONSOL18
CONSOL19
CONSOL20
CONSOL21
CONSOL22
CONSOL23
CONSOL24
CONSOL25
CONSOL26
CONSOL27
CONSOL28
CONSOL29
CONSOL30
CONSOL31
CONSOL32
CONSOL33
CONSOL34
CONSOL35

```

57345 04 03-16-77 17.022

```
36      10 FORMAT(I6)
37      CALL CNSLIO(CONSLW,MES1,11)
38      11 CALL CNSLIO(CONSLW,MES2,8)
39      CALL CNSLIO(CONSLW,MES21,9)
40      CALL CNSLIO(CONSLW,MES3,9)
41      CALL CNSLIO(CONSLW,MES0,11,NREPLY)
42      IF(NREPLY.EQ.NANS1.OR.NREPLY.EQ.NANS2) GO TO 12
43      IF(NREPLY.EQ.NANS5.OR.NREPLY.EQ.NANS8) GO TO 12
44      IF(NREPLY.EQ.NANS3.OR.NREPLY.EQ.NANS4) GO TO 13
45      IF(NREPLY.EQ.NANS7.OR.NREPLY.EQ.NANS8) GO TO 13
46      NREPLY=IZERO
47      GO TO 11
48      12 IREPLY=1
49      GO TO 14
50      13 IREPLY=0
51      14 RETURN
52      15 RETURN 1
53      ENTRY GONMES
54      CALL CNSLIO(CONSLW,MES,10)
55      RETURN
56      ENTRY GONGRT
57      CALL CNSLIO(CONSLW,MES5,9)
58      RETURN
59      END
```

CONSOL36  
CONSOL37  
CONSOL38  
CONSOL39  
CONSOL40  
CONSOL41  
CONSOL42  
CONSOL43  
CONSOL44  
CONSOL45  
CONSOL46  
CONSOL47  
CONSOL48  
CONSOL49  
CONSOL50  
CONSOL51  
CONSOL52  
CONSOL53  
CONSOL54  
CONSOL55  
CONSOL56  
CONSOL57  
CONSOL58  
CONSOL59

57345 04 03-16-77 17.024

```
1      CCLKTIM
2      SUBROUTINE BLKTIM(ITIME)
3      CALL PTIME(ATIME)
4      ITIME=ATIME*3600,
5      RETURN
6      END
```

ORIGINAL PAGE IS  
OF POOR QUALITY



```

1      CESTIII
2      SUBROUTINE ESTIM1(SUM1,SUM2,DELTA,BBIAS,PARNO1,PARTLI,NDX1,NDX2)
3      DOUBLE PRECISION SUM1(1),SUM2(1),DELTA(1),PARTLI(1),PARTLC(1),WT
4      DIMENSION BBIAS(1),BIASSG(3),SIGMA(1)
5      INTEGER PARNO1(1),PARVOC,SCRC,SNREV(1),KNSTR(1)
6      LOGICAL NEWARC
7      COMMON/TAPES/INTP,IOUT,GTAP,NSTAPE,SNTAPE,SCRB,SCRC
8      DATA NEWARC:/TRUE./
9      DATA BIASSG/0.001,2.10,7
10     INDXNO(1)=NDIM*(1-1)-(1*(1-1))/2
11     NPARI=NDX1
12     NPCOM=NPARI*NDX2
13     NDIM=NPARI*NPCOM
14     ISTART=NPARI+1
15     IEND=NPARI*2
16     I1=INDXNO(NDIM)+NDIM
17     CALL CLEAR(SUM1,2*I1)
18     CALL CLEAR(SUM2,2*NDIM)
19     RETURN
20     ENTRY ESTIM(PARNOC,PARTLC,SIGMA,RESID)
21     IF(SIGMA(1).LE.0.0.OR,SIGMA(2).LE.0.0) RETURN
22     IF(.NOT.NEWARC) GO TO 25
23     NSTORE=INDXNO(NPARI)+NDIM
24     CALL CLEAR(SUM1,2*NSTORE)
25     CALL CLEAR(SUM2,2*NPARI)
26     NEWARC=.FALSE.
27     DO 50 I=1,NPARI
28         I1=I+NPARI
29         PARTLI(I1)=PARTLC(I)
30     50 PARNO1(I1)=PARNOC+I
31         WT=1.0/(SIGMA(1)**2+SIGMA(2)**2)
32         DO 75 J=1,IEND
33             I1=PARNO1(I)
34             T=PARTLI(I1)*WT
35             SUM2(I1)=SUM2(I1)+T*RESID
36             DO 65 J=1,IEND
37                 IST=INDXNO(I1)+PARNO1(J)
38     65 SUM1(IST)=SUM1(IST)+T*PARTLI(J)
39     75 CONTINUE
40     RETURN
41     ENTRY ESTIMA(ICON)
42     IF(ICON.EQ.4) GO TO 100

```

57345 04 03-16-77 17.025

```

43      DO 85 I=1,CON,NPARI
44      I1=INDXNQ(I)+1
45      SUM1(I1)+SUM1(I1)+1.000/BIASSG(I)*#2
46      CALL SYMINV(SUM1,NDIM,NPARI,DELTA)
47      I1=INDXNQ(NSTART)
48      DO 200 I=NSTART,NDIM
49      L1=0
50      DO 160 L=1,NPARI
51      DELTA(L)=0.000
52      IST=0
53      DO 140 J=1,N
54      J1=IST+L
55      J2=IST+1
56      DELTA(L)=DELTA(L)+SUM1(J1)*SUM1(J2)
57      140 IST=IST+NDIM-J
58      IF(L>EQ,NPARI) GO TO 150
59      LP1=L+1
60      DO 145 J=LP1,NPARI
61      J1=L1+J
62      J2=IST+1
63      DELTA(L)=DELTA(L)+SUM1(J1)*SUM1(J2)
64      145 IST=IST+NDIM-J
65      150 SUM2(I)=SUM2(I)-SUM2(L)*DELTA(L)
66      DO 155 K=1,NDIM
67      K1=I1+K
68      K2=L1+K
69      155 SUM1(K1)=SUM1(K1)-DELTA(L)*SUM1(K2)
70      L1=L1+NDIM-L
71      J1=1
72      DO 175 J=1,NPARI
73      SUM1(J1)=DELTA(J)
74      175 J1=J1+NDIM-J
75      200 I1=I1+NDIM-1
76      IST=0
77      DO 250 I=1,NPARI
78      DELTA(I)=0.000
79      I1=1
80      DO 240 J=1,I
81      DELTA(I)=DELTA(I)+SUM1(I1)+SUM2(J)
82      240 I1=I1+NDIM-I
83      IF(I>EQ,NPARI) GO TO 248
84      IP1=I+1

```

ORIGINAL PAGE IS  
OF POOR QUALITY

```

85      DO 245 J=IP1,NPARI
86      I1=IST+J
87      245 DELTA(I)*DELTA(I)+SUM1(I1)*SUM2(J)
88      248 BBIAS(I)*BBIAS(I)+DELTA(I)
89      250 IST=IST+NDIM-I
90      WRITE(SCRC) (SUM1(I),I=1,NSTORE),(SUM2(I),I=1,NPARI),
91      , (BBIAS(I),I=1,NPARI)
92      NEWARC=.TRUE.
93      RETURN
94      ENTRY ESTIM0(SNREV,KNSTR,IKNSTR)
95      DO 300 I=1,NDX2
96      IJK=NUMBER(SNREV(I),KNSTR,IKNSTR)
97      IF(IJK.EQ.0) GO TO 300
98      L1=KNSTR(IJK+IKNSTR)
99      IF(L1.GT.NPARI) GO TO 300
100     DO 275 J=L1,NPARI
101     I1=NPARI*I+J
102     I1=INDXNO(I1)+I1
103     275 SUM1(I1)*SUM1(I1)+1.000/BIASSG(J)**2
104     300 CONTINUE
105     310 IST=INDXNO(NSTART)
106     I1=IST+NSTART
107     CALL SYMINV(SUM1(I1),NPCOM,NPCOM*DELTA(NSTART))
108     I2=IST
109     DO 350 I=NSTART,NDIM
110     DELTA(I)*0,DDO
111     I1=I2+I
112     DO 340 J=NSTART,I
113     DELTA(I)*DELTA(I)+SUM1(I1)*SUM2(J)
114     340 I1=I1+NDIM-I
115     IF(I,EQ,NDIM) GO TO 348
116     IP1=I+1
117     DO 345 J=IP1,NDIM
118     I1=IST+J
119     345 DELTA(I)*DELTA(I)+SUM1(I1)*SUM2(J)
120     348 BBIAS(I)*BBIAS(I)+DELTA(I)
121     350 IST=IST+NDIM-I
122     ENDFILE SCRC
123     REWIND SCRC
124     RETURN
125     ENTRY UPDATE
126     READ(SCRC) (SUM1(I),I=1,NSTORE),(SUM2(I),I=1,NPARI),

```

57345 04 03-16-77 17.025

```
127      . (BBIAS(I),I=1,NPARI)
128      I1=0
129      DO 500 I=1,NPARI
130      DELTA(I)=0,8DO
131      DO 450 L=NSTART,NDIM
132      L1=I1+L
133      450 DELTA(I)=DELTA(I)-SUM1(L1)*DELTA(L)
134      BBIAS(I)=DELTA(I)+BBIAS(I)
135      500 I1=I1+NDIM-1
136      RETURN
137      END
***&W 7 MEMORY EXCEEDED, USE $LIMITS OR CORE= OPTION FOR NEXT RUN
```

113

ORIGINAL PAGE IS  
OF POOR QUALITY

```

1  CSYMINV
2  C NAME          SYMINV
3  C
4  C PURPOSE      .TO RECURSIVELY FIND INVERSE OF SYMMETRIC MATRIX
5  C
6  C CALLING SEQUENCE  CALL SYMINV(SUM1,NDIM,NLIM,DELTA)
7  C
8  C      SYMBOL  TYPE  DESCRIPTION
9  C
10 C      SUM1    DP    INPUT = LOWER RECTANGULAR PART OF MATRIX
11 C      (1)                      TO BE INVERTED
12 C                          OUTPUT = LOWER RECTANGULAR PART OF INVERTED MATRIX
13 C
14 C      NDIM     I     INPUT = DIMENSION OF MATRIX
15 C
16 C      NLIM     I     INPUT = DIMENSION OF PARTITION TO BE INVERTED
17 C
18 C      DELTA    DP    SCRATCH
19 C      (1)
20 C
21 C SUBROUTINES USED  NONE
22 C
23 C COMMON BLOCKS     NONE
24 C
25 C INPUT FILES       NONE
26 C
27 C OUTPUT FILES      NONE
28 C
29 C REFERENCES        'GEODYN SYSTEMS DESCRIPTION'
30 C                   VOLUME 1 = GEODYN DOCUMENTATION
31 C
32 C
33 C
34 C
35 C      SUBROUTINE SYMINV(SUM1,NDIM,NLIM,DELTA)
36 C      DOUBLE PRECISION SUM1(1),DELTA(1)
37 C  INITIALIZE BY FINDING INVERSE OF 1X1
38 C      SUM1(1)=1.0D0/SUM1(1)
39 C      IF(NLIM,EQ,1) RETURN
40 C      N1=NDIM-1
41 C  RECURSIVELY FIND INVERSE OF NXN KNOWING INVERSE OF (N-1)X(N-1) UNTIL
42 C  THE INVERSE OF AN NLIM X NLIM SQUARE PARTITION IS FOUND

```

```

SYMINV01
SYMINV02
SYMINV03
SYMINV04
SYMINV05
SYMINV06
SYMINV07
SYMINV08
SYMINV09
SYMINV10
SYMINV11
SYMINV12
SYMINV13
SYMINV14
SYMINV15
SYMINV16
SYMINV17
SYMINV18
SYMINV19
SYMINV20
SYMINV21
SYMINV22
SYMINV23
SYMINV24
SYMINV25
SYMINV26
SYMINV27
SYMINV28
SYMINV29
SYMINV30
SYMINV31
SYMINV32
SYMINV33
SYMINV34
SYMINV35
SYMINV36
SYMINV37
SYMINV38
SYMINV39
SYMINV40
SYMINV41
SYMINV42

```

57445 04 03-16-77 17.028

```
43      DO 400 N=2,NLIM
44      NM1=N-1
45      L1=0
46      DO 100 L=1,NM1
47      J1=0
48      DELTA(L)=0.4D0
49      DO 60 J=1,L
50      JL=J1+L
51      JN=J1+N
52      DELTA(L)=DELTA(L)+SUM1(JL)+SUM1(JN)
53      60 J1=J1+NDIM-U
54      IF(L.EQ,NM1) GO TO 100
55      LP1=L+1
56      DO 80 J=LP1,NM1
57      JN=J1+N
58      JL=L1+J
59      DELTA(L)=DELTA(L)+SUM1(JL)+SUM1(JN)
60      80 J1=J1+NDIM-U
61      100 L1=L1+NDIM-L
62      J1=N
63      NN=N1+N
64      DO 150 J=1,NM1
65      SUM1(NN)=SUM1(NN)-DELTA(J)+SUM1(J1)
66      150 J1=J1+NDIM-U
67      SUM1(NN)=1.4D0/SUM1(NN)
68      J1=N
69      DO 200 J=1,NM1
70      SUM1(J1)=-DELTA(J)+SUM1(NN)
71      200 J1=J1+NDIM-U
72      I1=N
73      DO 300 I=1,NM1
74      J1=I
75      DO 250 J=1,I
76      SUM1(J1)=SUM1(J1)-SUM1(I1)+DELTA(J)
77      250 J1=J1+NDIM-U
78      300 I1=I1+NDIM-I
79      400 N1=N1+NDIM-N
80      RETURN
81      END
```

SYMINV43  
SYMINV44  
SYMINV45  
SYMINV46  
SYMINV47  
SYMINV48  
SYMINV49  
SYMINV50  
SYMINV51  
SYMINV52  
SYMINV53  
SYMINV54  
SYMINV55  
SYMINV56  
SYMINV57  
SYMINV58  
SYMINV59  
SYMINV60  
SYMINV61  
SYMINV62  
SYMINV63  
SYMINV64  
SYMINV65  
SYMINV66  
SYMINV67  
SYMINV68  
SYMINV69  
SYMINV70  
SYMINV71  
SYMINV72  
SYMINV73  
SYMINV74  
SYMINV75  
SYMINV76  
SYMINV77  
SYMINV78  
SYMINV79  
SYMINV80  
SYMINV81

115

ORIGINAL PAGE IS  
OF POOR QUALITY

## REFERENCES

1. Martin, T.V., W.F. Eddy, I.H. Oh, J.A. Kogut, "GEODYN System Description," prepared for NASA/GSFC under Contract No. NAS 5-22849, August 1976.
2. McMillan, J.D., "ARC Program Documentation," Wolf Research and Development Group, report prepared under Contract No. NAS 6-2173 for NASA/Wallops Flight Center, March 1976.
3. Amann, D.W., "ALTKAL Operations Manual," Wolf Research and Development Group, prepared under Contract No. NAS 6-2639 for NASA/Wallops Flight Center, January 1977.